



SERIES 1517 EU Compact

PRODUCT SPECIFICATIONS



1517 MODEL



Dimensions:
(width x Depth x height)
Height without feet:

14.7 x 17.2 x 4.0 inches
373 x 437 x 102 mm
3.8 inches or 97 mm

Shipping weight: 29 lbs
13.2 kg

FEATURES

- Dimensions accommodate a common European footprint
- 4 bill, 8 coin till accommodates a variety of currencies
- Single media slot
- Industrial grade, steel ball bearing slides
- Tested to last beyond 4 million operations
- Available in Black and Cloud White, with a painted drawer front
- Four function lock
- Closed and latched drawer status switch
- Random keying is standard, other lock and key options available

AVAILABLE INTERFACES

320 MultiPRO® 24 volt *
520 MultiPRO® III Dual 12/24 volt *

XXX Other numbers indicate the DirectPRO® hardwired or a custom interface

* Requires detachable cable sold separately. Refer to Connectivity Guide at www.apgcashdrawer.com for interface cable detail.

OPERATING ENVIRONMENT

Storage Temperature -30°C to +50°C (-22°F to +122°F)

Operating Temperature 0°C to +40°C (+32°F to +104°F)

Relative Humidity 10% to 95%
(non-condensing)

ACCESSORIES

Standard Till



VPK-15B-5-BX
4 bill, 8 coin
Fixed bill/coin widths
14.2 x 12.1 x 2.40 inch
361 x 321 x 61 mm

Locking Till Cover



VPK-14B-6-BX
Optional till cover improves security as it hides the contents of till from sight

Weighable Coin Cups



VPK-15J-01-BX
Standard tare weight for automated cash counting at 33.5 grams each cup

Under Counter Mounting Brackets



PK-27-D-BX
Optional kit provides a secure mounting system and frees up counter space

WARRANTY

Two (2) year limited warranty. A full warranty statement is available online at www.apgcashdrawer.com/support/warranty-statement.



APG Cash Drawer, LLC
5250 Industrial Blvd. N.E.
Minneapolis, MN 55421

Phone: 763 571 5000
Fax: 763 571 5771

APG® Cash Drawer, the APG Cash Drawer logo, SerialPRO®, MultiPRO®, DirectPRO®, USBPro™, ParallelPRO™, POS-Integrator™, Vasario™, POS-Podium™ and Cash Drawer Caddy™ are trademarks of APG Cash Drawer, LLC.

M-43-115 Rev. B