

## F502 Fanfold Color Label Printer

### Rugged Construction Meets Versatile Printing

The F502 is a small-footprint fanfold label printer, capable of producing durable, full-color labels on-demand. All-steel industrial design, improved toolbox functionality, over 2x faster printing, and optional durable pigment inks make the F502 extremely rugged and versatile.

The heavy-duty construction of the F502 color label printer includes a steel body with a window for print bed visibility and status monitoring. Improved sensors allow for greater compatibility with specialty media, such as reflective metallic material.

The F502's pigment inks have been tested and **certified to produce BS 5609-compliant and GHS (Globally Harmonized System) labels**, which helps keep chemical manufacturers in compliance with packaging and transportation requirements.

#### Key Features

- ✓ Pigment inks provide exceptional water, abrasion, and UV resistance
- ✓ Print vibrant and colorful prime labels with dye-based inks
- ✓ Industrial steel construction
- ✓ Flexibility to change label designs and content on the fly
- ✓ Best for short- to mid-sized print runs



[afinialabel.com](http://afinialabel.com)

**US Office**  
sales@afinialabel.com  
+1 888.215.3966



**UK Office**  
sales@afinialabel.co.uk  
+44 (0) 845.250.7949



**AFINIA LABEL®**

# F502 Specifications

## General:

<b>Print Technology:</b>	HP Thermal Inkjet
<b>Print Resolution:</b>	Up to 4800 dpi
<b>Print Speed:</b>	Approximately 5.2 in/sec (13.2 cm/sec) printing a 2.2 in (56 mm) wide image in plain paper normal mode
<b>Inks:</b>	Option of Dye or Pigment — Individual Cyan, Magenta, Yellow (26 mL), Individual Black (78.4 mL)
<b>Media Format:</b>	Fanfold
<b>Media Types:</b>	Compatible with wide range of paper, polyester, polypropylene, and vinyl label stocks. Supports gap, black mark, and continuous media
<b>Media Sensing:</b>	Auto calibration and auto detection of gap and black marks
<b>Label Width:</b>	1.0" – 8.5" (25.4 mm – 215.9 mm)
<b>Label Length:</b>	0.75" – 48" (19 mm – 1219.2 mm)
<b>Media/Liner Width:</b>	1.5" - 8.65" (38.1 mm – 219.7 mm)
<b>Inter Label Gap Size:</b>	0.125" – 0.3" (3.175 mm – 7.62 mm)
<b>Black Mark Size:</b>	0.125" – 0.3"
<b>Label Thickness:</b>	0.004" – 0.01" (0.1 mm – 0.3 mm)
<b>Cutter:</b>	Powered cutter
<b>Unwinder:</b>	8.5" (219.7 mm) max width, 8" (203 mm) OD on a 3" core (76.2 mm)
<b>Display:</b>	2" mono display with buttons
<b>Operating Systems:</b>	Windows 7, 8, and 10 (32 and 64 bit)
<b>Data Interface:</b>	USB 2.0 connection and 10/100 Base-Tx Ethernet
<b>Operating Temperature:</b>	59 – 90°F (15 – 32°C)
<b>Operating Humidity:</b>	20 – 80% RH
<b>Overall Dimensions:</b>	20" (511 mm) W, 23.5" (596 mm) D, 9.75" (248 mm) H
<b>Weight:</b>	40 lb (18.2kg)
<b>Warranty:</b>	1 year



### DURABLE LABELS

Use pigment-based inks for maximum durability



Waterproof



Abrasion Resistant



UV Resistant

### PRIME LABELS

Use dye-based inks for vibrancy and "pop"



Vibrant Color



Optimal Contrast



Eye Catching



[afinialabel.com](http://afinialabel.com)

US Office  
sales@afinialabel.com  
+1 888.215.3966



UK Office  
sales@afinia.co.uk  
+44 (0) 845.250.7949



AFINIA LABEL®