



CB-724e Barcode Printer



OVERVIEW

The Cub CB-724e is a unique, high performance desktop printer. With the CB-724e you don't have to sacrifice performance for size. This unit offers capabilities typically only found in more expensive larger footprint, mid-range industrial printers. The unit features the fastest print speed in its class of 7 inches per second. Additionally, the CB-724e includes Ethernet connectivity standard for easy network integration.

FEATURES

- Two Year Part & Labor Warranty
- Free Lifetime Technical Support
- Dual motor design
- Included external roll holder allowing 3" Core / 8" Outer diameter roll capacity
- Standard real time clock

Optional Factory-Installed Features Include:

- Peel-Off Module Assembly
- Guillotine Cutter Full or Partial Cut
- Linerless Cutter & Platen Kit
- Keyboard Display Unit / Printer Powered (KDU-100)
- Printer Powered, Long Range Linear Imaging Barcode Scanner (CS-9202)
- External Rechargeable Battery Pack (CB-100)

Included Accessories:

- Quick Start and User's Guide
- BarTender UltraLite Label Creation Software
- USB Interface Cable
- External Universal Switching Power Supply
- Power Cord
- 1" Core Label Roll Holder

- Ribbon Spindles
- Ribbon take-up core
- External Roll Holder with 3" Core Adapter

THE CB-724e IS IDEAL FOR:

- Nursing Stations
- Retail Price Marking - QuickBooks Compatible!
- Shipping and Inventory Control Label Printing
- Standalone Oil Change, Deli, Scan-and-Print
- Asset Label Printing
- UPC Product



REAR INTERFACE

CB-724e SPECIFICATIONS

PRINT METHOD	Direct Thermal/Thermal Transfer
RESOLUTION	203 DPI
PRINT SPEED (Inches per Second)	7
PROCESSOR	200MHz, 32-Bit RISC CPU
MEMORY	8MB DRAM, 4MB Flash, 4GB Expandable via SD Card
INTERFACE	Internal Ethernet, USB 2.0, RS-232C/9-Pin Serial, Centronics/Parallel
DIMENSIONS	12.36" (L) x 8.39" (W) x 7.40" (H)
SAFETY AGENCY APPROVAL	FCC, CE, C-Tick, UL, CUL, TUV, CCC
WARRANTY	2-Year Limited

ENVIRONMENT

OPERATION	41-401F / 5-40 C (20-85% non-condensing)
STORAGE	-40-140 F / -40-60 C (5-90% non condensing)

MEDIA CHARACTERISTICS

MAX. PRINT WIDTH	4.25"
MIN. PRINT WIDTH	.75"
MAX. PRINT LENGTH	90"
MIN. PRINT LENGTH	.375"
MAX. MEDIA THICKNESS	7.4 mil
MIN. MEDIA THICKNESS	2.3 mil
MEDIA TYPES	Continuous, Die Cut, Tag, Roll, Fanfold
SENSOR TYPE	Gap Transmissive, Adjustable Black Mark Reflective
MAX. ROLL DIAMETER	Internal: 4 or 5" External: 8.3"
CORE DIAMETER	Internal: 1" External: 3"
ROLL TYPE	Wound Out

RIBBON CHARACTERISTICS

MAX. RIBBON WIDTH	4.33"
MIN. RIBBON WIDTH	1.57"
RIBBON LENGTH	984"
CORE DIAMETER	1"
ROLL TYPE	Coated Side Out