CITIZEN
Micro HumanTech

Be unique
Stylish and flawless POS printers

CITIZEN CT-S251

MOBILE POSREADY
CITIZEN
Micro HumanTech

Chic
The CT-S251 is perfect for high class restaurants and boutiques where the environment requires a top class POS printer with eye-catching design. Choose between the white or black versions.

Fast
With its unique and stylish design, the two-inch CT-S251 POS printer is perfect for receipt or queue management systems. With a class-leading 300 mm/s print speed, front exit and compact size, the CT-S251 blends performance and poise.

Applications
- Receipts
- Queue management
- Weigh scales
- Coupons
- Daily reports
- Hospitality

Well connected
Connectivity is key with the possibility for USB, Serial, MFi Bluetooth®, Ethernet and WiFi interfaces and toolkit support for iOS™, Android™ and Windows® operating systems.That creates ideal conditions for easy integration.

Made for
iPod iPhone iPad

Citizen Systems America

CITIZEN
Micro HumanTech

Easy to use
Thanks to the robust yet user friendly design, the CT-S251 has quick and efficient paper loading, preventing paper jams.

CITIZEN CT-S251

Specifications

Model	CT-S251
Printing method	Line Thermal Dot Printing
Printing width	54mm/432 dots
Dot pitch	8 x 8 dots/mm (203 dpi x 203 dpi)
Number of columns	Up to 36 digits (12 × 24: font A), Up to 48 digits (9 × 24: font B), Up to 54 digits (8 × 16: font C)
Printing speed	Max. 300mm/sec., When greyscale printing: 130mm/sec
Line spacing	4.23mm (1/6 inch); adjustable by user comand
Barcode type	UPC-A, UPC-E, JAN / EAN-8, JAN / EAN-13, ITF, CODE39, CODE93, CODE128, CODABAR (NW-7), PDF417, QR Code, GS1 Databar.
Emulation	ESC/POS™®
Paper	Width	57.5 +/- 0.5mm / 2.26 +/- 0.02in
	Diameter	83mm / 3.27in or less
	Thickness	53µm to 85µm
	Recommended Paper	Mitsubishi Paper Mills P220AG normal type 65, HP220AB-1 highly conserved type 75, F230AA normal type 65, P220AB normal type 85, Oji Paper PD150R normal type 75, PD160R high storage type 65/75, Nippon Paper TF50KR-2Y high storage type 62, TR50KJ-R high-save type 63
Power adapter	37AD2 (AC Adapter)
AC input voltage	AC 100 to 240V, 50/60 Hz, 150 VA
DC operating voltage	24V DC ±7%, supplied by AC adapter
Weight	1.20 Kg / 2.65 lb
Dimension (W x D x H)	108 x 165 x 108 mm +5mm front lip / 4.25 x 6.49 x 4.25 in +0.2in front lip footprint
Operating environment	+5 to 45°C / +41 to 113°F, 10%-90% RH, non condensing
Storage environment	-20 to 60°C / -4 to 140°F, 10%-90% RH, non condensing

Features & Benefits

- Front Exit
- Fast 300 mm/sec
- 2-inch media: 57.5 ± 0.5 mm
- MFi / iOS™ Bluetooth® version
- WiFi and Ethernet versions
- ENERGY STAR® power supply
- Stylish black or white case
- Same height as cash drawers
- Cash drawer connection
- ESC/POS™® compatibility
- SDKs for iOS™, Android™, Windows®

Citizen Systems America