

High-speed industrial printing



### Space-saving design concept

The Hi-Open™ case lifts up vertically meaning that the printer's footprint does not change as the cover is opened making it ideal for tight spaces.

### Optional peeler

An optional peeler can be added to the CL-S700 giving the peel-and-present function without the height of the full liner rewinder case.

### Easy configuration

The large graphic LCD gives a clear indication of printer status and easy printer configuration.

## CL-S700

Label, Industrial

### Applications

- Logistics / Transport
- Courier
- Manufacturing
- Retail
- Warehousing



High performance with easy access

# CITIZEN

## Specifications

| Model                        | CL-S700  |
|------------------------------|--|
| Printing Technology          | Thermal Transfer + Direct Thermal  |
| Resolution                   | 203 dpi  |
| Print Speed (maximum)        | 10 inches per second (254 mm/s)  |
| Print Width (maximum)        | 4 inches (104 mm)  |
| Media Width (min to max)     | 1 to 4 inches (25 to 118 mm)   |
| Roll Size (max), Core Size   | Outside diameter 8 inches (200 mm) Core size 1 inch (25mm) Plus Outside media slot                                 |
| Media Thickness (min to max) | 63.5 to 254 µm   |
| Media Length (min to max)    | 0.25 to 32 inches (6.35 to 812.8 mm)   |
| Media Sensor                 | Fully adjustable rear sensor and high resolution front sensor  |
| Main Interface               | Triple interface USB, parallel and serial built-in, exchangeable interface card slot for optional card             |
| Interface                    | Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT) |
| Ribbon size                  | 3.4 inches (86.5 mm) maximum outside diameter. 450 meter length  |
| Ribbon winding & type        | Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type  |
| Ribbon system                | ARCP™ automatic ribbon tension adjustment  |
| Mechanism                    | Hi-Lift™ metal mechanism with wide opening head  |
| Control panel                | 4 buttons, 4-line back-lit graphic LCD   |
| Emulations (Languages)       | Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400                        |
| Drivers and software         | Free-of-charge on CD with printer, including support for various platforms   |

## CL-S700

### Label, Industrial

#### Features & Benefits

- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.
- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Recyclable packaging
- Basic peeler



Ingeniously designed for easy operation and reliability

# CITIZEN

## CL-S700

Label, Industrial

|                                    |  |
|------------------------------------|--|
| <b>Model</b>                       | <b>CL-S700</b>                                   |
| <b>Flash (Non-Volatile Memory)</b> | 4 MB total, 1 MB available for user              |
| <b>Size (W x D x H) and Weight</b> | 255 x 490 x 265 mm, 13.3 Kg                      |
| <b>Warranty</b>                    | 2 years on printer. 6 months or 50 Kms printhead |

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0