# MEMOR™ 10

Google

DATALOGIC

E & 5.45

ş





If you are looking for the power and the performance of a smartphone but are concerned about the typical Enterprise challenges, the new Datalogic Memor 10 PDA is the perfect rugged device for you!

Memor 10 incorporates the latest smartphone technologies and the user friendly experience of Android™ in a slim and compact design, combined with high performance 1D/2D bar code scanning and industrial robustness for almost any indoor or outdoor environment.

#### **TOP PERFORMANCE**

The Memor 10 is powered by a superior octa-core platform clocked at 2 GHz for top performance with the most demanding applications, and features Android 8.1 (Oreo) with Google Mobile Services (GMS).

Moreover, the Memor 10 is one of the first rugged mobile computers to be validated by Google for the 'Android Enterprise Recommended' program for rugged devices.

#### WIRELESS CHARGING MEETS SWAPPABLE BATTERY

The Memor 10 incorporates Datalogic's industry-first wireless charging system for ultra-reliable contactless charging, thus eliminating the need for cleaning contacts on the device and docks. Moreover, Memor 10 offers a 1-piece swappable battery for the best operational advantage.

## COMMUNICATIONS

The Memor 10 leverages a complete set of embedded wireless technologies for both indoor and outdoor applications: dual band Wi-Fi including the latest 802.11ac standard, Bluetooth® v4.2 with BLE for fast and ultra-low power connections, NFC for easy pairing, and particularly the cellular area voice and data connectivity, already leveraging the next generation of LTE-Advanced/4G+.

NOTE: The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

## **FEATURES**

- Ultra-Ergonomic, compact and robust
- 5 inch capacitive multi-touch HD display with Dragontrail<sup>™</sup> hardened glass
- Android 8.1 (Oreo) with Google Mobile Services
- · Wireless charging eliminates all contacts on the device and cradle

memorio

- Ruggedized with drop resistance to 1.5m / 5ft to concrete and IP65 sealing
- Dual band Wi-Fi including the latest 802.11ac standard and 802.11r/k for fast roaming

android enterprise

recommended

- Full suite of cellular connectivity for voice and data, featuring LTE-Advanced/4G+
- Assisted GPS for location based apps
- Bluetooth v4.2 short range wireless technology
- NFC for proximity communications
- Advanced 2D ultra-slim imager with Datalogic's patented 'Green Spot' technology for visual good-read feedback
- Datalogic's SoftSpot<sup>™</sup> technology for innovative triggering through the touch display
- Chemical resistant plastics / enclosure designed to withstand daily cleaning with harsh disinfectant solutions
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI





#### **Industry - Applications**

- Retail:
  - Assisted sales
  - Inventory
  - Access control
  - Shop floor applications
  - Mobile POS
- T&L:
  - Route accounting
  - Direct store delivery
  - Workforce management
  - Courier value-added services
- Manufacturing:
  - Production and quality control
  - Intra-logistics
  - Inventory
  - Field maintenance
- Healthcare: Bedside care
  - Pharmacv

  - Inventory management Labs

GREEN

# MEMOR™ 10 TECHNICAL SPECIFICATIONS

## WIRELESS COMMUNICATIONS

WIRELESS COMMU	NICATIONS
Local Area Network (WLAN)	IEEE 802.11 a/b/g/n/ac and 802.11 k/r/v; Frequency range: Country dependent, typically 2.4 GHz and 5 GHz bands
Personal Area Network (WPAN)	Bluetooth wireless technology v4.2 (Classic Bluetooth wireless technology and BLE)
NFC Communication	Support for the following standards: ISO14443-4 (type-A, type-B); ISO15693; Mifare; Felica
WWAN / Cellular	LTE-Advanced / 4G+; Cat 6
DECODING CAPABI	LITY
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
2D Codes	Aztec Code, Data Matrix, HanXin Code, MaxiCode, MicroQR Code, QR Code, UPU FICS, USPS Intelligent Mail
Postal Codes	Australian Post, Japan Post, KIX Code, PLANET, POSTNET, Royal Mail Code (RM4SCC)
Stacked Codes	Micro-PDF417, PDF417, GS1 DataBar Composites, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional
ELECTRICAL	
Battery	Replaceable battery pack with rechargeable Li-Ion batteries; 3.8v; 4,100 mAh (15.6 Watt-hours)
Wireless Charging	Qi Compliant; 10 Watt fast charging
ENVIRONMENTAL	
Drop Resistance	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test.
Tumbles	Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot
Particulate and Water Sealing	IP65
Chemical Resistance	Chemical cleanser and industrial oil resistant (both Standard and Healthcare models)
Healthcare Cleanable	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and cradles
Temperature	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F
INTERFACES	
Interfaces	High Speed USB 2.0 Host and Client with USB Type C connector
SENSORS	
Vibration	Software programmable for duration and intensity
Accellerometer	3-Axis accelerometer to detect orientation
Gyroscope	Senses angular velocity
Ambient Light	Auto adjusts display backlight
Proximity	Auto deactivates display when close to face

PHYSICAL CHARAC	TEDICTICS	
Dimensions	15.5 x 7.8 x 1.87 cm / 6.1 x 3.07 x 0.73 in	
Display	5 inch IPS HD resolution 720 x 1280; LED backlight; Touch Screen: 5 points multi-touch capacitive panel with Dragontrail hardened glass	
Keys	Physical Keys: 2 side scan keys; Power On/Off; Volume Up/ Down; 3 user programmable Android™ keys	
Weight	With Battery: 285.0 g / 10.0 oz	
READING PERFORM	READING PERFORMANCE	
Camera	Resolution: 13 megapixel; Illumination: User controllable LED flash; Lens: Auto focus	
Scan Engine	2D Ultra slim area imager (supports 1D / 2D codes); Datalogic's 'Green Spot' for good-read feedback; Depth of Field: 8.5 to 50 cm / 3.3 to 19.7 in depending on bar code density and type; Resolution: VGA (640 x 480 pixels); Illumination: White LEDs; Aiming: 650nm VLD; Field of View: 48°H x 34°V	
Print Contrast (Minimum)	25%	
Minimum Element Width	1D Linear: 0.0762 mm / 4 mils PDF: 0.127 mm / 6.6 mils Data Matrix: 0.195 mm / 7.5 mils	
SAFETY & REGULA	TORY	
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.	
Environmental Compliance	Complies to EU RoHS	
SOFTWARE		
Applications	Datalogic's SoftSpot technology for configurable soft triggers; Supports Datalogic's Queue Busting app; Pre-licensed device and browser lockdown powered by	
	42Gears; Enterprise class PTT offered by Zello	
Provisioning		
Provisioning Configuration and Maintenance	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or	
Configuration and	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware	
Configuration and Maintenance	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC	
Configuration and Maintenance Development	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC Java and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Wavelink	
Configuration and Maintenance Development MDM	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC Java and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Wavelink Avalanche, 42Gears SureMDM	
Configuration and Maintenance Development MDM Terminal Emulation	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC Java and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Wavelink Avalanche, 42Gears SureMDM	
Configuration and Maintenance Development MDM Terminal Emulation SYSTEM	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC Java and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Wavelink Avalanche, 42Gears SureMDM StayLinked SmartTE, Wavelink Velocity Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible;	
Configuration and Maintenance Development MDM Terminal Emulation SYSTEM Expansion Slots	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC Java and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Wavelink Avalanche, 42Gears SureMDM StayLinked SmartTE, Wavelink Velocity Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible; SIM SLOT MicroSIM Standard size	
Configuration and Maintenance Development MDM Terminal Emulation SYSTEM Expansion Slots Memory	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC Java and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Wavelink Avalanche, 42Gears SureMDM StayLinked SmartTE, Wavelink Velocity Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible; SIM SLOT MicroSIM Standard size System RAM: 3 GB; eMMC Flash: 32 GB	
Configuration and Maintenance Development MDM Terminal Emulation SYSTEM Expansion Slots Memory Microprocessor	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC Java and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Wavelink Avalanche, 42Gears SureMDM StayLinked SmartTE, Wavelink Velocity Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible; SIM SLOT MicroSIM Standard size System RAM: 3 GB; eMMC Flash: 32 GB 2 GHz Octa-core	
Configuration and Maintenance         Development         MDM         Terminal Emulation         SYSTEM         Expansion Slots         Memory         Microprocessor         Operating System	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC Java and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Wavelink Avalanche, 42Gears SureMDM StayLinked SmartTE, Wavelink Velocity Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible; SIM SLOT MicroSIM Standard size System RAM: 3 GB; eMMC Flash: 32 GB 2 GHz Octa-core Android v8.1 with GMS	
Configuration and Maintenance         Development         MDM         Terminal Emulation         SYSTEM         Expansion Slots         Memory         Microprocessor         Operating System         Real-Time Clock	42Gears; Enterprise class PTT offered by Zello Android Zero Touch enrollment and QR Code or NFC Bump provisioning Datalogic DXU for device configuration and firmware upgrade from PC Java and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Wavelink Avalanche, 42Gears SureMDM StayLinked SmartTE, Wavelink Velocity Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible; SIM SLOT MicroSIM Standard size System RAM: 3 GB; eMMC Flash: 32 GB 2 GHz Octa-core Android v8.1 with GMS	

# ACCESSORIES Base Stations/Chargers















94A150095 Single Slot Dock

94A150096 3-Slot Dock

94ACC0192 Battery Charger

92 Charger

94A150097 94ACC0201 Vehicle Dock Attachable Pistol Grip

94ACC0193 Rubber Boot

© 2018-2019 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. • Memor is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. • Memor is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. • Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. • The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. • All other trademarks and brands are property of their respective owners • Product specifications are subject to change without notice. • DS-MEMOR10-ENA4 Revision B 20190129