



## DPM TECHNOLOGY

Direct Part Marking (DPM) is a process that allows users to imprint a bar code directly on an item instead of printing the code on a paper label. Different technologies are available to directly mark objects: laser / chemical etching, dot peening and ink jet printing. Each of these methods have specific advantages and disadvantages in terms of durability, cost and ease of reading.

The PowerScan™ 9500-DPM product series are rugged handheld area imagers specifically addressed and capable of reading codes marked with DPM.

## READING CAPABILITIES

The PowerScan DPM series include the latest optics and software from Datalogic to make the reading of codes with DPM easy and intuitive. The typical reading distance is from contact to 4-5 cm / 1.5-1.9 in, depending on the DPM technology used, the code resolution, and the material and surface type.

The scanner is also capable of reading standard bar codes on printed labels. High density optics allow the capture of very small, high-resolution codes in a range from near contact up to 15.0 cm / 5.9 in.

## SOFT WHITE ILLUMINATION

The intuitive aiming system provides the highest first-pass reading rates. A soft-pulsed white illumination light results in reduced flashes and is very gentle to the eyes.

## MOTIONIX™ MOTION-SENSING TECHNOLOGY

Datalogic's Motionix™ motion-sensing technology detects the natural actions of the operator to automatically switch the scanner into the desired scanning mode.



### FEATURES

- Supports any kind of Direct Part Marked (DPM) code
- Snappy omnidirectional reading
- Intuitive aiming system
- Soft white light illumination
- Datalogic's Motionix™ motion-sensing technology
- Ergonomic shape
- Image capture
- Datalogic's 3GL™ (3 Green Lights) technology and loud beeper for good-read feedback
- Water and Particulate Sealing Rating: IP65
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI
- **Cordless Products**
  - Bluetooth® 2.0 Compliant: Class 1 or Class 2 configurable via software

### INDUSTRY-APPLICATIONS

- Manufacturing Shop Floor
  - Work-in-Progress
  - Sub-Assembly
  - Component Tracking
  - Quality Control
  - Time and Cost Analysis
  - Line Inventory Control

## DECODING CAPABILITY

|                   |   |
|-------------------|---|
| 1D / LINEAR CODES | Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes   |
| 2D CODES          | Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code   |
| POSTAL CODES      | Postnet; Royal Mail Code (RM4SCC)   |
| STACKED CODES     | EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites |

## ELECTRICAL

|               |   |
|---------------|---|
| CURRENT       | Operating (Typical): 350 mA<br>Standby/Idle (Typical): 120 mA |
| INPUT VOLTAGE | 5 VDC +/- 10%   |

## ENVIRONMENTAL

|                                |   |
|--------------------------------|---|
| AMBIENT LIGHT                  | 0 - 100,000 lux   |
| DROP RESISTANCE                | Withstands 50 drops from 2.0 m / 6.6 ft onto a concrete surface                           |
| ESD PROTECTION (AIR DISCHARGE) | 20 kV   |
| HUMIDITY (NON-CONDENSING)      | 0 - 95%   |
| PARTICULATE AND WATER SEALING  | IP65  |
| TEMPERATURE                    | Operating: -20 to 50 °C / -4 to 122 °F<br>Storage/Transport: -40 to 70 °C / -40 to 158 °F |

## INTERFACES

|            |   |
|------------|---|
| INTERFACES | RS-232 / USB / Keyboard Wedge Multi-Interface |
|------------|---|

## PHYSICAL CHARACTERISTICS

|                  |   |
|------------------|---|
| COLORS AVAILABLE | Yellow/Black; Other colors and custom logo options are available for minimum quantity purchase. |
| DIMENSIONS       | 21.2 x 11.0 x 7.4 cm / 8.3 x 4.3 x 2.9 in   |
| WEIGHT           | 330.0 g / 11.6 oz   |

## READING PERFORMANCE

|                                      |   |
|--------------------------------------|---|
| DIRECT PART MARKING (DPM) CAPABILITY | Codes are readable when marked by laser or chemical etching or ink jet printed; Data Matrix codes are also readable when marked by dot peening  |
| IMAGE CAPTURE                        | Graphic Formats: BMP, JPEG, TIFF<br>Greyscale: 256, 16, 2; JPEG, TIFF   |
| IMAGER SENSOR                        | 864 x 544   |
| LIGHT SOURCE                         | Aiming: 630 - 680 nm VLD<br>Illumination: White LED reading light   |
| PRINT CONTRAST RATIO (MINIMUM)       | 15%   |
| READING ANGLE                        | Pitch: +/- 40°; Roll (Tilt): 360°; Skew (Yaw): +/- 40°  |
| READING INDICATORS                   | Beeper (Adjustable Tone and Volume); Datalogic's 3GL™ (Three Green Lights) technology and loud beeper for good-read feedback; Datalogic 'Green Spot' on the Code; Dual Good Read LEDs |
| RESOLUTION (MAXIMUM)                 | 1D Codes: 2.5 mil; 2D Codes: 4 mil  |

## READING RANGES

### TYPICAL DEPTH OF FIELD

Depth of Field ranges on bar codes printed with DPM technology may vary depending on the printing technology, the code type and the resolution of the code. Other factors include the surface material the DPM technology is used on (metal, plastic, shiny or polished, opaque, etc.). The following specs represent standard bar codes that are traditionally printed black on white on paper labels.

|                     |                                |
|---------------------|--------------------------------|
| 2 mils              | 2.8 to 6.3 cm / 1.1 to 2.4 in  |
| 2.5 mils            | 2.5 to 7.8 cm / 0.9 to 3.0 in  |
| 5 mils              | 1.2 to 9.0 cm / 0.4 to 3.5 in  |
| 4 mils Data Matrix  | 2.6 to 5.2 cm / 1.0 to 2.0 in  |
| 5 mils Data Matrix  | 2.2 to 7.2 cm / 0.8 to 2.8 in  |
| 10 mils Data Matrix | 2.0 to 10.5 cm / 0.8 to 4.1 in |
| 5 mils PDF          | 1.2 to 9.0 cm / 0.4 to 3.5 in  |
| 10 mils PDF         | 1.0 to 12.5 cm / 0.4 to 4.9 in |
| 13 mils EAN-13      | 2.5 to 16.0 cm / 0.9 to 6.3 in |

## SAFETY & REGULATORY

|                          |  |
|--------------------------|--|
| AGENCY APPROVALS         | The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. |
| ENVIRONMENTAL COMPLIANCE | Complies to China RoHS; Complies to EU RoHS; Complies to R.E.A.C.H.  |
| LASER CLASSIFICATION     | Caution Laser Radiation - Do not stare into beam<br>CDRH Class II; IEC 60825 Class 2   |
| LED CLASSIFICATION       | IEC 62471 Class 1 LED  |

## UTILITIES

|                      |   |
|----------------------|---|
| DATALOGIC ALADDIN™   | Datalogic Aladdin configuration program is available for download at no charge.                                       |
| OPOS / JAVAPOS       | JavaPOS Utilities are available for download at no charge.<br>OPOS Utilities are available for download at no charge. |
| REMOTE HOST DOWNLOAD | Available on request  |

## WARRANTY

|          |                         |
|----------|-------------------------|
| WARRANTY | 3-Year Factory Warranty |
|----------|-------------------------|

## CORDLESS COMMUNICATIONS

|                               |   |
|-------------------------------|---|
| BLUETOOTH WIRELESS TECHNOLOGY | Piconet: Max. Readers per Radio Receiver Using Commercial Dongle: 7; Using Cradle: 4  |
| PROFILES                      | HID (Human Interface Device)  |
| PROTOCOL                      | SPP (Serial Port Profile)   |
| RADIO FREQUENCY               | Bluetooth 2.0 Certified Class 1 or Class 2 (Configurable)   |
| RADIO RANGE (OPEN AIR)        | 2.40 to 2.48 GHz  |
|                               | Class 1: Exceeds 90 m/295 ft  |
|                               | Class 2: Exceeds 40 m/131 ft  |
|                               | Range distances are measured using the base station. Range with connection to other Bluetooth peripherals may show different results. |
| SECURITY                      | Data Encryption; Scanner Authentication   |

## DECODING CAPABILITY

|                   |   |
|-------------------|---|
| 1D / LINEAR CODES | Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes   |
| 2D CODES          | Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code;  |
| POSTAL CODES      | Australian Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Portuguese Post; Postnet; Royal Mail Code (RM4SCC); Swedish Post;   |
| STACKED CODES     | EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites |

## ELECTRICAL

|                        |  |
|------------------------|--|
| BATTERY                | Battery Type: Lithium-Ion 2150 mAh<br>Charge Time: External Power: 4 Hours; Host Power: 10 Hours |
| READS PER CHARGE       | Continuous Reading: 30,000+  |
| CRADLE INDICATOR LEADS | Battery Charging (Red); Charge Completed (Green); Power/Data (Yellow)                            |
| CURRENT                | Charging (Typical): External Power: 800 mA @ 10 VDC; POT: 500 mA @ 5 VDC                         |
| OPERATING (TYPICAL)    | 150 mA @ 10 VDC  |
| INPUT VOLTAGE          | External Power: 10-30 VDC; POT: 5 VDC +/- 10%  |

## ENVIRONMENTAL

|                                |   |
|--------------------------------|---|
| AMBIENT LIGHT                  | 0 - 100,000 lux   |
| DROP RESISTANCE                | Cradle: Withstands 50 drops from 1.2 m / 6.6 ft onto a concrete surface<br>PBT9500-DPM: Withstands 50 drops from 2.0 m / 3.9 ft onto a concrete surface |
| ESD PROTECTION (AIR DISCHARGE) | 20 kV   |
| HUMIDITY (NON-CONDENSING)      | 95%   |
| PARTICULATE AND WATER SEALING  | IP65  |
| TEMPERATURE                    | Operating: -20 to 50 °C / -4 to 122 °F<br>Battery Charging: 0 to 45 °C / -32 to 113 °F  |
| STORAGE/TRANSPORT              | -40 to 70 °C / -40 to 158 °F  |

## INTERFACES

|            |   |
|------------|---|
| INTERFACES | Keyboard Wedge RS-232; RS-485;<br>USB: OEM USB; USB COM; USB HID Keyboard |
|------------|---|

## PHYSICAL CHARACTERISTICS

|                  |   |
|------------------|---|
| COLORS AVAILABLE | Yellow/Black  |
| DIMENSIONS       | Cradle: 24.0 x 10.8 x 9.5 cm / 9.4 x 4.3 x 3.8 in<br>PBT9500: 21.2 x 11.0 x 7.4 cm / 8.3 x 4.3 x 2.9 in<br>PBT9500: 380.0 g / 13.4 oz |
| WEIGHT           |   |

## READING PERFORMANCE

|                                      |  |
|--------------------------------------|--|
| DIRECT PART MARKING (DPM) CAPABILITY | Codes are readable when marked by laser or chemical etching or ink jet printed; Data Matrix codes are also readable when marked by dot peening   |
| IMAGE CAPTURE                        | Graphic Formats: BMP, JPEG, TIFF;<br>Greyscale: 256, 16, 2   |
| IMAGER SENSOR                        | 864 x 544  |
| LIGHT SOURCE                         | Aiming: 630 - 680 nm VLD<br>Illumination: White LEDs   |
| PRINT CONTRAST RATIO (MINIMUM)       | 15%  |
| READING ANGLE                        | Pitch: +/- 40°; Roll (Tilt): 360°; Skew (Yaw): +/- 40°   |
| READING INDICATORS                   | Beeper (Adjustable Tone and Volume);<br>Datalogic's 3GL™ (Three Green Lights) technology and loud beeper for good-read feedback; Datalogic 'Green Spot' on the Code, Dual Good Read LEDs |
| RESOLUTION (MAXIMUM)                 | 1D Codes: 2.5 mil; 2D Codes: 4 mil   |

## READING RANGES

**TYPICAL DEPTH OF FIELD**  
Depth of Field ranges on bar codes printed with DPM technology may vary depending on the printing technology, the code type and the resolution of the code. Other factors include the surface material the DPM technology is used on (metal, plastic, shiny or polished, opaque, etc.). The following specs represent standard bar codes that are traditionally printed black on white on paper labels.

|                     |                                |
|---------------------|--------------------------------|
| 2 mils              | 2.8 to 6.3 cm / 1.1 to 2.4 in  |
| 2.5 mils            | 2.5 to 7.8 cm / 0.9 to 3.0 in  |
| 5 mils              | 1.2 to 9.0 cm / 0.4 to 3.5 in  |
| 4 mils Data Matrix  | 2.6 to 5.2 cm / 1.0 to 2.0 in  |
| 5 mils Data Matrix  | 2.2 to 7.2 cm / 0.8 to 2.8 in  |
| 10 mils Data Matrix | 2.0 to 10.5 cm / 0.8 to 4.1 in |
| 5 mils PDF          | 1.2 to 9.0 cm / 0.4 to 3.5 in  |
| 10 mils PDF         | 1.0 to 12.5 cm / 0.4 to 4.9 in |
| 13 mils EAN-13      | 2.5 to 16.0 cm / 0.9 to 6.3 in |

## SAFETY & REGULATORY

|                          |  |
|--------------------------|--|
| AGENCY APPROVALS         | The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. |
| ENVIRONMENTAL COMPLIANCE | Complies to China RoHS; Complies to EU RoHS; Complies to R.E.A.C.H.  |
| LASER CLASSIFICATION     | Caution Laser Radiation - Do not stare into beam<br>CDRH Class II: IEC 60825 Class 2   |
| LED CLASSIFICATION       | IEC 62471 Class 1 LED  |

## UTILITIES

|                      |   |
|----------------------|---|
| DATALOGIC ALADDIN™   | Datalogic Aladdin configuration program is available for download at no charge                                    |
| OPOS / JAVAPOS       | JavaPOS Utilities are available for download at no charge; OPOS Utilities are available for download at no charge |
| REMOTE HOST DOWNLOAD | Available on request  |

## WARRANTY

|          |                         |
|----------|-------------------------|
| WARRANTY | 3-Year Factory Warranty |
|----------|-------------------------|

## DPM TECHNOLOGY

Direct Part Marking (DPM) is a process for imprinting a bar code directly on an item or surface in a permanent manner instead of printing the code on a paper label that is adhered or attached to a surface. The intent is to create a permanent identifier for the item.

The main benefit of DPM technology is its durability. The permanent nature of the marking assures that the item can be identified throughout its full life cycle and throughout the supply chain, even while being exposed to harsh environmental conditions. Another important benefit of DPM technology is that it allows the marking of very small codes in limited spaces where a standard label cannot be applied in a reliable and stable mode.

Bar codes marked with DPM can be implemented on different surfaces and materials including plastic, metal, wood, rubber, leather, glass, etc.

DPM technology is used to enhance the supply chain traceability of car components, medical tools, military and defense equipment, fine jewelry, electronic parts or any application where there is the need to experience harsh chemical treatment, endure extreme conditions of moisture or temperature, include high-value assets or items that need to be identified throughout their lifetime.




## DIFFERENT MARKING TECHNOLOGIES

There are multiple methods for directly marking objects:

- Laser Etching
- Chemical Etching
- Dot Peening
- Ink Jet Printing

Each of these methods has specific advantages and disadvantages in terms of durability, cost and ease of reading.


## EXAMPLES OF DPM MARKED CODES




Laser Etching



Chemical Etching



Dot Peening



Ink Jet Printing

## ACCESSORIES

### Base Stations/Chargers



▪ BC9030-BT: Base/Charger, Multi-Interface



▪ BC9130-BT: Base/Dual Charger, Multi-Interface

### Cases/Holsters



▪ HLS-P080: Universal Holster (HLS-8000)

### Mounts/Stands



▪ HLD-P080 Desk/Wall Holder (HLD-8000)



▪ 7-0404 Industrial Take-Up Reel



BARCODE  
FACTORY

## **Barcode Factory**

*A Paragon Print Systems Company*

**2021 Paragon Drive | Erie PA 16510**  
**814.456.8331 | Toll Free: 888.237.8525**  
**info@barcodefactory.com**