# Andes 3



### features at a glance 🗉 🖬 🗖

**Rugged Design – The durable Andes** 3 has a flame retardant heavy-duty housing that is chemical and UV resistant and comes with side and corner over-molding to withstand multiple drops to 4 feet (1.2 meters).

Affordable - Standard features and accessories included with the Andes 3 include USB, RS232, Bluetooth, battery, AC adaptor, shoulder strap and a one year warranty.

Fast Printing - All features supported by the Andes 3 are managed by a 7-Arm, 32 bit RISC processor ensures fast print speed of up to 3" (76mm) per second.

**User Controlled Memory – All resident** fonts and firmware are integrated into the printer's memory meaning the 4MB Flash and 2MB memory is available to store your logos, fonts, graphics and barcodes.

Easy to Use - Simplified LED lights indicate Power/Communication, Battery Status/Charging, options and error. It holds a paper roll of up to 130ft (40m) and a simple "drop-in" paper load system allows for quick paper roll replacement. Transparent door inserts let you see when paper roll is running low.

Options - IrDA, 802.11b/g, and magnetic card reader.

Endurance - A high-capacity lithiumion batters lasts a full shift on a single battery charge.

Graphics - Supports the printing of graphics, 1D and 2D Symbologies.

**Charging Options - Standard: AC** adaptor included with printer. Optional: vehicle charger, vehicle mount and external 2-Bay batter charger.

# 3" Rugged Receipt Printer

The Datamax-O'Neil Andes 3 printer was designed for the rough and tumble environment of the mobile field worker. Rugged, lightweight and easy to use, the Andes 3 is the perfect choice for companies who need a durable printer at an affordable price.

The Andes 3 is lightweight and compact with all the features and options necessary to keep pace with today's changing requirements in field service, law enforcement, retail, hospitality and route accounting applications. The Andes 3 can be worn comfortably all day with a shoulder strap or swivel belt loop. Its large paper capacity and easy "drop-in" paper loading means less downtime and higher efficiency. The Andes 3 is powered by a high-capacity, long lasting Lithium-Ion battery that lasts through an 8 - 10 hour shift. The Arm-7, 32 bit architecture RISC processor allows receipts to print quickly with ample memory for logos, graphics, fonts and barcodes.

The affordable Andes 3 comes equipped with USB, RS232 and Bluetooth as well as a universal AC adaptor, shoulder strap, battery, spare paper roll and includes a one year warranty (including printhead). Options include IrDA, Wi-Fi, 3-Track magnetic card reader as well as a variety of accessories. With its low price point, the Andes 3 offers the options and features of higher priced products without compromising on quality and strength.

### popular applications



Travel **Payment Receipts** Ticketing



# **Field Service**

 Service Receipts - Credit Card Receipts - Pick-ups/Deliveries

# - Signature proofs

#### Did you know?

Using quality paper can significantly prolong the life of your printhead. Datamax-O'Neil offers 7 grades of high quality receipt paper for the Andes 3 Printer. When you choose Datamax-O'Neil Certified Supplies you receive a proven commitment to superior quality that results in performance and compatibility...Guaranteed.



#### Mobile POS

- Credit Card Transactions
- Transaction Receipts
  - **Queue Busting**

#### Route Accounting


- Delivery Receipts
- Inventory Reports
- Credit Card
- Transactions

## vour benefits 🔳 🔳

#### Ruggedness and affordability -

The Andes 3 is a proven design that has earned a reputation for durability in applications around the world. With its affordable pricing, the Andes 3 offers companies the options and features of higher priced printers without compromising on quality and performance.





#### physical characteristic • •

- Dimensions
- 6.9" L x 4.8" W x 3.5" H (175 x 123 x 86 mm)
- Weight:
  - Printer with battery: 23 oz (0.779 kg)
     Printer with battery & paper roll:
- 33.6 oz (0.953 kg)
- Drop specifications: 4 ft. (1.2 m)

#### user environment

- Operating Temperature: 14° to 122°F (-10° to 50°C)
- Storage temperatures: -4° to 140°F (-20° to 60°C)
- Charging temperatures: 41° to 104°F (5° to 40°C)
- Relative humidity range:
   10% RH to 85% RH non-condensing
- ESD Protection: 8kV Air/ 4kV Contact

#### print technology • • •

- Printhead:
  - Direct Thermal
  - 203 dots per inch (8 dots per mm)
- Print mechanism speed:
   3 inches per second (76 mm per second)
- Print width:
- 2.83" (72 mm)

#### media • • •

- Media Type:
  - Direct thermal receipt paper (standard, premium, heavy duty, long-life, image protect, hi-temp, and all weather)
  - For optimum print quality and printer performance, use Certified Datamax-O'Neil supplies
- Paper Width:
- 3.15" (80 mm)
- Max Roll Size:
- 2.2" (55mm) maximum roll diameter (0.D.)
- Max Media Thickness:
- 6 mil
- Media I.D. Core:
   0.4" (10 mm)

#### communication • •

- Serial:
- RS232, up to 460.8 kbps
- USB:
- 2.0
- Bluetooth:
- Version 2.0
- 802.11 b/g: (optional)
  - Frequency band 2.400 to 2.490 GHz
  - Data rates up to 54 Mbps
  - Network standard: IEEE 802.11 b/g
  - Wireless access modes: Infrastructure and ad-hoc
  - Security Protocols:

		WPA	WPA2
	Modes	PSK/Enterprise	
	Security/Encryption	TKIP/RCA	CCMP/AES
	Authentication	LEAP	

– Network support: DHCP, TCP, UDP

#### barcodes/fonts/graphics • •

- Memory:
- 2MB RAM / 4MB Flash
- Linear: Codes 39, Code128 A/B/C, UCC/EAN-128, Interleaved2 of 5, UPC/EAN/JAN and Codabar
- 2D Symbologies: PDF417
- Optional characters: Simplified & Traditional Chinese, Hebrew, Arabic, Polish, Greek, Cyrillic
- Graphics: Supports 8-bit graphic printing, custom font, logo downloading
- Standard fonts:
- ASCII, International, PC Line draw
   12CPI, 16CPI, 19CPI, 21CPI, 24CPI,13CPI rotated

#### power source • •

#### Battery:

- (1) 7.4V Lithium-Ion, 2200 mAhDC Input (for charging only):
- External DC jack, 10V, built-in spike and surge protection
- Endurance:
- Serial: prints approx. 969 6" receipts
   Bluetooth: prints approx. 936 6" receipts
- Recharging:
- 3 hours from AC adapter or cigarette adapter

#### software • •

- · Configuration Utility includes:
- Font Download
- Bluetooth® Set-up
- Wi-Fi Set-Up
- Communications Parameter set-up
- Printer Custom Attributes Set-up
- Logo Download
- Drivers:
- Windows, CE and Desktop
- Form Fiesta Page Printing Utility
- Bootloader for Uploading Firmware

#### options • • •

- 802.11 b/g
- Integrated magnetic strip card reader

#### accessories • •

Andes 3 comes complete with Belt Loop, Battery, Universal AC Adapter and 1 Roll of Media.

- Replacement Battery Li-Ion 7.4V 2200 mAh
- Belt Loop System or Shoulder Strap System

   Carry the printer comfortably either on your belt or on the shoulder
- Cigarette Lighter Adapter Allows you to charge the printer from the vehicle cigarette lighter
- USB Cable USB data cable with gold plated contacts
- Battery Charger 2 Bay battery charger for charging Li-Ion batteries (batteries not included)
- Cleaning Cards Use of clean card is recommended to extend the life of the printhead

#### agency approval

Contact sales manager for the most current approval list

#### warranty • • •

- Printer\*: 1 year (including platen roller and installed options)
- Printhead\*: 1 year or 1,000,000 inches whichever comes first
- Contact sales representative for extended warranty options

\*when used with approved supplies



#### **ED** Specifications subject to change without notice. Copyright 2010, Datamax-O'Neil (rev. 20100706a)

to learn more. visit www.datamax-oneil.com

A DOVER Company

