



# Elo Pay 15" 'Tap to Pay'

Integrated Payment POS



**Integrated NFC for  
contactless payments**



**Android 14**



**Enterprise-Grade  
Support**

## Product Overview

Discover seamless transactions with the Elo Pay 15-inch integrated payment solution. The self-service platform pairs a Full HD touch display with integrated NFC, Android 14, and the Qualcomm SD6490 processor to deliver fast, reliable performance. From self-order and self-checkout to ticketing and customer check-in, deploying kiosks has never been easier. Pair the Elo Pay 15-inch with a variety of stands and mounts to create the self serve solution your business needs.

With no need for complex payment certifications and access to immediate integration, it's never been easier to start transacting. Start changing the way customers and employees interact by deploying a new generation of interactive technologies that provides seamless integration, effortless provisioning and simplified device management via EloView™ or your preferred management tools.

**Integrated NFC offers Full EMV L1  
Compliance to accept payments**

**Universal VESA mount allows the Elo  
Pay 15" to mount on a variety of  
stands, pole mounts and wall mounts.**

**Optional PoE adapter simplifies  
installation with power and data over  
a single cable**

**Configure for a variety of applications  
with four Elo Edge Connect™ ports  
integrated along the display edges**

Elo Pay 15" 'Tap to Pay' POS System

| Specifications             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Enclosure Color            | Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Diagonal Size              | 15.6" / 396.24 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Active Display Area        | 13.55" x 7.62" / 344 mm x 194 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Resolution                 | 1920 x 1080 @ 60Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Touch Technology           | TouchPro™ PCAP (Projected Capacitive) - up to 10 touches                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Touch Through              | TouchPro PCAP supports up to 6mm glass / 3mm plastic with up to 2 touches                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Aspect Ratio               | 16:9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Number of Colors           | 8-bit (16.7M)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Brightness                 | LCD Panel: 300 nits; PCAP: 258 nits                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Response Time              | 30 ms                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Viewing Angle              | Horizontal: ±85° or 170° total / Vertical: ±85° or 170° total                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Contrast Ratio             | 800:1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Operating System           | Android 14 with Google Play Services and EloView content deployment and management<br>Planned upgrade to Android 16 and Android 18 are available with an OS 360 subscription                                                                                                                                                                                                                                                                                                                                                                                            |
| Processor                  | Qualcomm QCS6490                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Memory                     | 8GB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Storage                    | 64GB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| I/O Ports                  | 1x USB-A 3.0 support (900mA)<br>USB-C output*<br>Micro SD slot, GPIO<br>RJ45 Ethernet LAN (Gigabit)<br>DC in<br>4x micro-USB 2.0 Elo Edge Connect ports (Support for 1.2A on one port and 500mA for the remaining three ports)<br><br>* When using the standard 65W power brick, USB-C can support up to 15W. When using the optional 90W power brick, USB-C can support up to 27W. See User Manual for details                                                                                                                                                         |
| Wireless                   | 802.11a/b/g/n/ac/ax + Bluetooth 5.2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| NFC                        | Front facing NFC antenna<br>Programmable rear-lit white LED illuminates NFC contactless logo<br>Fully SoftPOS compatible                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Webcam                     | 8MP, Max Resolution: 3264x2448 30fps, Auto Focus                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Speakers                   | 2x1.5W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Audio                      | 2x built-in Digital Microphones                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Power                      | AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Power                      | Supported via Elo PoE Device PN: E669163                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Power Consumption          | On: 9.2W; Off: 0.2W; Sleep: 2.0W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Dimensions (W x D x H)     | 17.92" x 9.8" x 0.9" / 455.2 mm x 249.7 mm x 22.3 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Shipping Dimensions        | 21.6" x 6.3" x 13.4" / 548 mm x 160 mm x 340 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Weight                     | 4.0 lbs / 1.81 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Shipping Weight            | 8.4 lbs / 3.8 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Temperature                | Operating: 32°F to 104°F / 0°C to 40°C; Storage: -4°F to 122°F / -20°C to 50°C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Humidity                   | Operating: 20%-80%; Storage: 10%-90%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Mounting Options           | VESA 75mm and 100mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Real-Time Clock            | Lithium coin cell battery for real time clock                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Sealing                    | Touchscreen sealed to LCD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Warranty                   | 2 year standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Extended Warranty          | 3 yr OS 360 - Elo P/N: E897877, 4 yr OS 360 - Elo P/N: E898079, 5 yr OS 360 - Elo P/N: E898282<br>3 yr - Elo P/N: E819394, 4 yr - Elo P/N: E819598, 5 yr Coverage - Elo P/N: E819795<br>3 yr + ADP - Elo P/N: E130329, 4 yr + ADP - Elo P/N: E130530, 5 yr + ADP - Elo P/N: E130719<br>2 yr + AUR - Elo P/N: E819985, 3 yr + AUR - Elo P/N: E820186, 4 yr + AUR - Elo P/N: E820388, 5 yr + AUR - Elo P/N: E820582<br>2 yr + AUR + ADP - Elo P/N: E131490, 3 yr + AUR + ADP - Elo P/N: E131674, 4 yr + AUR + ADP - Elo P/N: E131859, 5 yr + AUR + ADP - Elo P/N: E132053 |
| Security Updates           | Bi-monthly Android security updates available with Elo OS 360 package                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Regulatory Approvals       | UL/cUL (US); FCC (US); IC (Canada); CE (Europe); CB (International); VCCI, MIC (Japan); RCM (Australia); BSMI/NCC (Taiwan); NOM (Mexico)                                                                                                                                                                                                                                                                                                                                                                                                                                |
| GMS Supported Country List | Canada, USA, Australia, Japan, New Zealand, Austria, Belgium, Czech Republic, Denmark, France, Germany, United Kingdom, Hungary, Italy, Netherlands, Poland, Portugal, Romania, Spain, Sweden, Switzerland, Turkey, Brazil                                                                                                                                                                                                                                                                                                                                              |
| What's in the Box          | Elo Pay 15", NA Power Cable, EU Power Cable, 1x Power Brick, Quick Install Guide, Screws for cable cover door                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

Ordering Information

| Part Number | Product Description  |
|-------------|----------------------|
| E488611     | Elo Pay 15" with NFC |

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000  
[elosales.na@elotouch.com](mailto:elosales.na@elotouch.com)

Europe (EMEA)

Tel +32 16 930 136  
[EMEA.Sales@elotouch.com](mailto:EMEA.Sales@elotouch.com)

Asia Pacific

Tel +86 (21) 3329 1385  
[EloAsia@elotouch.com](mailto:EloAsia@elotouch.com)

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, Elo Edge Connect, EloView and TouchPro are trademarks of Elo Touch Solutions, Inc., registered in many jurisdictions worldwide. Android is a trademark of Google LLC. Google Mobile Services is a trademark of Google LLC. © 2026 Elo Touch Solutions, Inc. All rights reserved. 26051AES00225





BARCODE  
FACTORY

## **Barcode Factory**

*A Paragon Print Systems Company*

**2021 Paragon Drive | Erie PA 16510**

**814.456.8331 | Toll Free: 888.237.8525**

**[info@barcodefactory.com](mailto:info@barcodefactory.com)**