


SECUREHEAD



MAGSTRIPE READ HEAD MODULE

KEY FEATURES:




- Incorporates ID TECH's state-of-the-art TriMag III ASIC:
 - Allows electronics to be embedded in read head
 - Performs magnetic strip recording
 - Contains microprocessor to handle encryption & communications for multiple interfaces
- Built-in encryption engine supports TDES & AES with DUKPT mkey management
- Multiple spring designs supported
- Ultra compact & tamper resistant design
- Durable to over 1,000,000 swipes



SECUREHEAD SPECS

CARD SPEED	3 to 75 Inches per Second
CURRENT	Active Power Supply Current: 7 mA Standby Power Supply Current: 5 mA Sleep Power Supply Current: USB Sleep 4000 μ A
DIMENSIONS	48.2mm (L) x 12.20mm (W) x .20mm (H)
ESD	+4kV Discharge to Head Can
HUMIDITY	Maximum 95% Non-Condensing
INTERFACE	SPI, UART, USB-HID, USB-KB
OPERATING LIFE	1,000,000 Cycles Minimum
OPERATING TEMPERATURE	-20°C to 70°C
POWER	Operating Voltage 3V or 5V \pm 10%
STORAGE TEMPERATURE	-40°C to 70°C
WARRANTY	One Year, Parts & Labor
WEIGHT	5.67 Grams



CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
T: (714) 761-6368
TF: (800) 984-1010
F: (714) 761-8880
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED

IDTECH®

Value through Innovation

IDTECHPRODUCTS.COM

