


AUTO-SENSOR1D BARCODE READER

Today's market demands high-performance barcode reading with speed, accuracy and data integrity. ID TECH's latest mid-range 1D barcode scanner is the ValueScan III, which is ideal for any merchant environment looking to support barcode reading with a scanning range up to 12 inches from the barcode. The ValueScan III features an autosensing mode, allowing the scanner to operate while resting in its stand. When the scanner detects a barcode is present, it will automatically activate, allowing users the freedom of scanning barcodes without a scanner in their hands. With two hands free to manage other tasks, the ValueScan III provides added productivity.











VALUESCAN III SPECS

DIMENSION

102mm x 71mm x 177mm

WEIGHT

190g

INTERFACES

USB HID, USB Virtual COM

INDICATORS

LED beeper

PROCESSOR

1GHz, X1500

IMAGE SENSOR

CMOS 1280*800

POWER REQUIREMENTS

5.0 VDC +/- 10%

SCAN RATE

270 times per second

LIGHT SOURCE

RED LED 620nm-630nm

RANGE

350mm +/- 50mm

APPROVALS

FCC, CE, BSMI

OPERATING

-20C to 50C

TEMPERATURE

STORAGE **TEMPERATURE** -40C to to 70C

HUMIDITY

5% to 95% (non-condensing)

DROP TEST

1.5m

CONTACT US TODAY!

CORPORATE HEADQUARTERS 10721 WALKER STREET

CYPRESS, CA 90630 TEL: (714) 761-6368 TF: (800) 984-1010

SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN) ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368 SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA EMEA@IDTECHPRODUCTS.COM

SYMBOLOGIES

Matrix 2 of 5

UPC-A

Plessey

Extended

Code 11

UPC-E

MSI

Aviation25

ISBN

■ EAN-8

• Code 93

GS1 Limited

ISSN

Codabar

Code 128

SISASI and RSS14

Code39

Code 39 Full ASCII
 Industrial 2 of 5

• GS1-128 and ITF-14

Code32 (Italian)
 China Post

Interleave 2 of 5
 GS1 Omnidirectional

ISO 9001 CERTIFIED ISO 14001 CERTIFIED

