

NETMark IQ Near Edge Wax-Resin

Wide Ranging Print Performance



Food/Beverage



Health/Beauty



Industrial



Logistics



Medical



Retail



The printhead cleaner built in your ribbon.

Benefits

- Compatible with Toshiba TEC, Novex and other near-edge printers.
- Dark black barcodes and images with solid fill and no show-through
- Broad stock latitude from rough vellum to smooth synthetics
- Fast print speeds
- Low to mid energy range prolongs printhead life
- Wax/Resin formula provides good resistance to abrasion
- Clean Start® built-in printhead cleaner maintains print quality
- Can be used in flexible packaging coders (See NETFlex+)

Recommended Stocks

Paper

- Vellum
- Matte Coated
- Semi-Gloss
- Gloss

Synthetics

- PP / Polypropylene
- PE / Polyethylene
- Polyolefin (e.g. Tyvek)

Applications

- Compliance labeling
- Component identification
- Flexible packaging
- Hang tags
- Ingredient lists
- Medical devices
- Pallet labeling
- Product identification
- Shelf marking
- Shipping
- Warehousing
- Work in process (WIP)

Key Product Range

STANDARD WAX	ENHANCED WAX	WAX RESIN	RESIN	NEAR EDGE
SW150 SW200	GP725 DC100	PM255 PM308 DC200	SP330 SP575 DC400	NETMark IQ NETFlex+ NETFlex+ XL NET330 NETColour

Technical Specifications

Colour Code Tab Copper
 Film Thickness 4.5 Microns
 Total Ribbon Thickness 8.0 Microns
 Transmission Density 1.1 MacBeth Scale
 Ink Melting Point 70°C / 158°F

Imaging Characteristics

Printhead Near Edge
 Max Print Speed 24 IPS (610 mm/s)
 Image Darkness 1.7 RD (densitometer)
 Heat Resistance Moderate

Compliance

- REACH – SVHC Free
- RoHS
- FDA GRAS Recognized
- FDA 21CFR175
- ISEGA

Storage Conditions

12 months recommended
 20-85% Relative Humidity Rate, -5-40°C (23-104°F)

Performance Ratings

