

RRR-330 SERIES REWINDERS

The RRR-330 Series Reel-to-Reel Unwinders / Rewinders provide a convenient way to reverse the wind direction of your rolls (Wind-In / Wind-Out) and re-tension your rolls, in a self-contained table-top package. Designed for all-day, every-day use, these Reel-to-Reel Unwinders / Rewinders are backed by a 3-Year Parts and Labor Limited Warranty, assuring you reliable performance for many years to come.



RRR-330

Technical Specifications	RRR-330	RRR-330-A
Max Media Width (in) ¹	6 (152-mm)	
Min Media Width (in)	N/A	
Max Label Length (in)	N/A	
Min Label Length (in)	N/A	
Max Roll Weight (lbs)	17 (8-kg)	
Max Roll Diameter (in)	13 (330-mm)	12.5 (317-mm)
Core Diameter (in) ²	3 (76-mm)	3 Unw; 1 - 4 Rwd (76; 25 - 102-mm)
Label Type	Any	
Liner Type	Any	
Max Speed (ips)	114 (2895-mm)	108 (2743-mm)
Min Speed (ips)	0.125 (3-mm)	
Max RPM	168	
Max Torque (in-oz)	1,837	
Dimensions-HWD (in)	14.5 x 32.5 x 13 (368 x 825 x 330-mm)	13 x 32.5 x 13 (330 x 825 x 330-mm)
Weight (lbs)	33 (15-kg)	34 (15.4-kg)
Power Specifications	120-220VAC in, 24VDC 100W out	
Warranty	3 year limited warranty on Reel-to-Reel Rewinder - 1 year limited warranty on Power Adaptor	
Available Options	<ul style="list-style-type: none"> • TSN-RR-6 (Tensioning Kit for pre-2016 models) • RR-1"U (Unwind Shaft for 1" Cores) ³ • RR-1.5"U (Unwind Shaft for 1.5" Cores) ³ • ROLLER KIT, RR-8" (8" Roller Kit) • ROLLER KIT, RR-10" (10" Roller Kit) 	

1. Maximum Media Width can be increased by adding either the 8" (203-mm) or 10" (254-mm) Roller Kit. 09.2016
 2. The RRR-330-A is equipped with an Adjustable Core Holder for 1" - 4" (25 - 102-mm) Diameter Cores.
 3. This option Modifies the standard 3" (76-mm) diameter Unwind Core Holder to the dimension specified.