



**UCAT-1-STANDARD**

## UCAT-1-STANDARD • UCAT-1-W10

The UCAT-1 Series Non-Powered Unwinders provide a convenient way to manage your supply roll of labels with a small amount of tension control. These Non-Powered Unwinders allow you to use larger supply rolls thereby minimizing your per unit label cost. The supply roll also doesn't have to be refreshed as often thus saving time and adding convenience.

Technical Specifications	UCAT-1-STANDARD	UCAT-1-W10
Max Roll Diameter (in)	12 (305-mm)	
Core Diameter (in)	3 (76-mm)	
Max Media Width (in)	6 (152-mm)	10 (254-mm)
Max Roll Weight (lbs)	17 (432-mm)	
Dimensions-HWD (in)	14 x 12 x 17 (355 x 305 x 432-mm)	14 x 12 x 19 (355 x 305 x 482-mm)
Weight (lbs)	25 (635-mm)	27 (686-mm)
Max Speed (ips) <sup>1</sup>	N/A	
Min Speed (ips) <sup>1</sup>	N/A	
Max Torque (in-oz) <sup>1</sup>	N/A	
Max RPM <sup>1</sup>	N/A	
Number of Flanges	1	
Power Specifications <sup>1</sup>	N/A	
Warranty	5 year limited warranty	
Available Options	<ul style="list-style-type: none"> <li>• FLANGE, CAT, OUT (Optional Outer Guide Flange)</li> </ul>	

1. The **UCAT-1** is Non-Motorized, Non-Powered