



PAL86518H-FNF/ PAR86518H-FNF

Circular Polarity Wide Band RFID Antenna

865-956 MHZ 8.5 DBIC CIRCULAR POLARITY PANEL

The Laird PAL86518H-FNF/PAR86518H-FNF antennas are circularly polarized panel antennas that provide reception and transmission of signals in the 865-956 MHz frequency band. Laird's industry renowned design methodology achieves maximum efficiency and performance across the entire frequency band.

Both VSWR and axial ratios are excellent and allow the user to achieve the maximum performance for an antenna of this type. The antenna is housed in a heavy duty radome enclosure that can be directly wall mounted. An optional articulating mount allows either wall or mast mounting.

The antenna is offered with a Fix N connector.

FEATURES TROHS

- · Low profile
- Extremely low VSWR and axial ratio Wide band
- Weather and UV resistant radome

- Wide range of connector and cable options Left hand and right hand CP versions
- IP 67


APPLICATIONS

- Warehouse
- Distribution center
- Airports and hospitals

- Transit terminals
- Conveyer belt

SPECIFICATIONS	
Antenna Part Number	PAL86518H/PAR86518H
Frequency Range	865 - 956 MHz
Gain	8.5 dBic
Maxium VSWR	1.5:1
3 dB Beamwidth - Azimuth	65°
Front to Bank Ratio	20dB
Polarization	Circular Right-hand or circular Left-hand
Maxium Input Power	3 Watts
Input Impedence	50 Ohms
Axial Ratio	1dB

SPECIFICATIONS	
Weight (Kg)	1.89 lbs (0.86)
Mechanical Size	10.2" x 10.2" x 1.32"
Antenna Connection	Fix N
Radome	High Strenght PC
Mount Style	Threaded Stud
Temperature Operational	-25°C to +70°C
Lighting Protection	DC Grounded
Environmental Rating	IP 67



TE TECHNICAL SUPPORT CENTER

USA: +1 (800) 522-6752 +1 (905) 475-6222 Canada: Mexico: +52 (0) 55-1106-0800 Latin/S. America: +54 (0) 11-4733-2200 Germany: +49 (0) 6251-133-1999 +44 (0) 800-267666 UK: +33 (0) 1-3420-8686 France: Netherlands: +31 (0) 73-6246-999 China: +86 (0) 400-820-6015

te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warrantied to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original

