



Li logic controls Li logic controls

FEATURES

- + Reliable performance
- + Sturdy design and easy operation
- + 17in projected capacitive touch panel
- + Automatic brightness control
- + Positive locking tilt angles
- + High contrast with 500:1 ratio
- + Built-in universal power supply
- + USB interface
- + VESA mount

LE1017-J

Touch Screen Monitor

and other valuable operations.

The LE1017-J 17 inch touch monitor is built to meet the requirements that leading retailers and restaurant operators need from their Point of Sale system. With the Projected capacitive touch panel, a high 500:1 contrast ratio and up to SXGA 1280X1024 resolution, the screen offers clear visibility for easy and efficient operations. The touch screen is highly rugged and stable, built for continuous use. The unit includes a solid base and a locking tilt mechanism so that the angle of the touch screen does not change during usage. Futhermore, the LE1017-J offers multimedia functions thanks to its incorporated speakers, allowing for the playback of training videos

logiccontrols.com



LE1017-J specifications

LCD TOUCH PANEL

LCD size: 17in (43.1cm)
Brightness: 300 cd/m²
Response time: 8ms.
Contrast ratio: 500:1

Resolution: SXGA (1280 x 1024)
Viewing angle: -5° dip and 20° elevation

Touch screen: Projected capacitive touch | USB interface

CONNECTOR

VGA (video): D-sub 15-pins Audio: Internal Speakers Power Cable: A/C Input

ELECTRICAL

Power supply: Built-in Universal Power Supply | 100-240 VAC, 50/60 Hz

Power consumption: Active < 48 Watt Max.
Saving mode: Standby < 3 Watt

ENVIRONMENTAL

Operating temperature: 32°F to 113°F (0°C to 45°C)

Storage temperature: 68°F to 140°F (20°C to 60°C) for standard LCDs

Humidity: 10~90% non-condensing

MECHANICAL

Net Weight: 11.9 lbs (5.4 Kg)

Dimensions (WxHxD): 15.6in x 15.2in x 9.3in (39.6cm x 38.5cm x 23.5cm)

Color: Black

CERTIFICATION UL / cUS, CE, FCC/B

MISCELLANEOUS VESA DPMS