



LV400U

FEATURES

- + 8" LCD display with LED backlight
- + Optimal display resolution, 800 x 600
- + No ventilation hole design
- + Light weight, only 1.5lbs for display (without the pole and base)
- + Simple installation
- + VESA 75 x 75mm wall mount standard
- + True flat panel screen

LCD Pole Display

The LV4000U is a customer price display with a bezel-free, true flat panel screen, compact in size and designed to be eco-friendly. The 8in LCD monitor can be used to deliver marketing and promotion messages to customers at time of checkout. With a high 500:1 contrast ratio and 800 x 600 optimal resolution, the screen projects vivid graphics to grab customer attention at the Point of Sale, enhancing the overall business experience.

logiccontrols.com



LV4000U specifications

MECHANICAL

Weight: 3.0 lbs (1.3 kg)

Dimensions (WxHxD): 15.7in x 7.9in x 5.9in (39.8cm x 20.0cm x 14.9cm)

Stand base: 7in (17.7cm) pole + base Wall mount: VESA 2.9in x 2.9in (7.5 x 7.5cm)

LCD MONITOR

Display size: 8in (20.3cm)

Active area: 6.3in x 4.7in (16.2cm x 12.1cm)

Optimal resolution: 800 x 600
Brightness: 230 cd/m²
Contrast ratio: 500:1
Response time: 25 ms

LCD viewing angle

Horizontal: 140° Vertical: 120°

Input signal connector: USB Type B

Input frequency: Horizontal: 31.5-60.2 kHz

Vertical: 56.3Hz - 75Hz

ELECTRICAL

Power consumption: USB 2.5W

Power supply: USB - Port Powered DC 5V +/- 10%

ENVIRONMENTAL

Operating temperature: 32°F to 104°F Storage temperature: 14°F to 122°F

Humidity: Operating: 20%~80%

Storage: 10%~90%