



FEATURES

- + True-flat, bezel-free, fanless design
- + 16:9 widescreen 15.6in LCD (1366x768)
- + High performance Intel Quad-Core processor
- + Durable and sturdy base
- + Easy to change or replace the SSD
- + Optional MSR and VFD/LCD customer display

SB1015W

True-flat 15.6in Touch Screen POS Terminal

The SB1015W is a cost effective 15.6in true-flat touch screen All-in-One Point-of-Sale terminal. The terminal packs great features and value into a sleek and sturdy design. It delivers an economical POS solution while providing excellent performance and reliability. The highly rugged touch monitor includes a solid base with extra wide hinge for maximum stability. The SB1015W also facilitates options for quick and professional mounting of integrated magnetic stripe reader and VFD/LCD customer display.



SB1015W specifications

MAINBOARD

CPU:	Intel Celeron J1900 Quad-Core 2.0GHz
IO chipset:	Intel IT 8718F-S
Memory:	DDR3L 1333 SODIMM slot, up to 8GB
Ethernet LAN:	Realtek RTL8111G PCI Express Gigabit LAN
Audio:	ALC887 Audio CODEC, HD Audio CODEC
Storage:	SSD, mSATA SSD

DISPLAY

Touch screen:	Projected capacitive touch
Touch controller:	USB interface
LCD panel:	15.6in TFT display, WXGA 1366x768, 200 nits

I/O PORTS

USB ports:	USB 2.0 x4, USB 3.0 x2
Serial ports:	RS232 DB9 x2
Ethernet:	Gigabit, RJ45 x1
Video port:	VGA DB15 x1
Audio port:	Line out x1

ELECTRICAL

Power supply:	DC 12V 80W min. External power adapter,
Input to power adapter:	100 to 240VAC, 50/60Hz

ENVIRONMENTAL

Operating temperature:	32°F to 104°F (0°C to 40°C)
Relative humidity:	8% to 80%, non-condensing

MECHANICAL

Dimensions (W x H x D):	15.9in x 12.1in x 9.0in (40.6cm x 30.8cm x 23.0cm)
Weight:	13lbs (5.91Kg)

OPTIONAL PERIPHERALS

Customer display:	VFD 20 columns x 2 lines (USB) or 8in true-flat LCD (VESA holes 75x75, USB)
MSR:	JIS-I or II, ISO Track 1/2/3 (USB)

