



WIRELESS 2D BARCODE SCANNER

NLS-HR3000-BT

Scanning made simple.

A cordless take on the HR3000 engine, the HR3000-BT captures high-density, high-volume and damaged barcodes over a stable Bluetooth 5.0 link. Built into an IP52-sealed, 1.5 m drop-resistant housing, its replaceable 2600 mAh battery keeps productivity up and downtime down.

NEWLAND AIDC, AVAILABLE THROUGH VERITRONICS



FEATURES

Reliable, Stable Wireless

Bluetooth 5.0 with strong anti-interference transmits data reliably up to 100 m in direct line of sight.

Replaceable Battery

A swappable 2600 mAh pack runs 15 hours of continuous use and minimizes downtime between shifts.

Outstanding Performance

An outstanding CPU effortlessly captures high-density, high-volume and distorted barcodes on paper or screen.

KEY SPECIFICATIONS

Image Sensor	1280×800 CMOS	Dimensions (L×W×H)	117.5×67.5×144mm (4.63×2.66×5.67in, scanner)
Radio Technology	Bluetooth 5.0	Weight	210g (7.41oz, scanner)
Communication Distance	100m / 328ft (line of sight)	Drop	1.5m (4.92ft)
Battery	2600 mAh · 15 hrs continuous	Sealing	IP52
Interface	USB Type-A	Operating Temperature	-10°C to 50°C (14°F to 122°F)

Technical Specifications

NLS-HR3000-BT

PERFORMANCE

Image Sensor	1280×800 CMOS
Illumination	White LED
Aiming	Laser diode
Symbologies	2D: PDF417, QR Code, Micro QR, Data Matrix, Aztec, Maxi Code, Chinese Sensible Code, GM Code, Micro PDF417, Code One 1D: Code 11, Code 128, Code 39, GS1-128 (UCC/EAN-128), AIM 128, ISBT 128, Codabar, Code 93, UPC-A, UPC-E, Coupon, GS1 Composite, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, ITF-6, ITF-14, Standard 2 of 5, China Post 25, MSI-Plessey, Plessey, GS1 Databar (RSS), Code 49, Code 16K Postal: USPS Postnet, USPS Intelligent Mail, Royal Mail, USPS Planet, KIX Post, Australian Postal · OCR: Passport, Chinese ID Card, China Travel Permit
Resolution*	≥3 mil (0.076mm / 0.003in)
Typical Depth of Field*	EAN-13 (13mil): 40–535mm (1.57–21.06in) · Code 39 (5mil): 50–230mm (1.97–9.06in) · PDF417 (6.7mil): 45–215mm (1.77–8.46in) · Data Matrix (10mil): 30–245mm (1.18–9.65in)
Scan Angle**	Pitch: ±60°, Roll: 360°, Skew: ±65°
Field of View	Horizontal 48°, Vertical 30°
Min Symbol Contrast*	15%

WIRELESS

Communication Mode	Synchronous, asynchronous and batch mode
Radio Technology	Bluetooth 5.0
Communication Distance	100m / 328ft (direct line of sight in open air)
Memory Capacity	16,384 pieces

PHYSICAL

Battery	2600 mAh lithium-ion battery
Expected Charge Time	6 hours (with power adapter)
Expected Battery Life	15 hours continuous (scan once per 6 s)
Interface	USB Type-A (USB-KBW, USB-CDC, HID-POS)
Operating Voltage	5VDC±5%
Dimensions (L×W×H)	Scanner: 117.5×67.5×144mm (4.63×2.66×5.67in) · Cradle: 140×90×144.5mm (5.51×3.54×5.69in)
Weight	Scanner: 210g (7.41oz) · Cradle: 340.5g (12.01oz)
Notification	Beep, LED indicator, vibration

ENVIRONMENTAL

Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Battery Charge Temperature	0°C to 45°C (32°F to 113°F)
Humidity	5%–95% (non-condensing)
ESD	±15kV (air discharge); ±8kV (direct discharge)
Drop	Scanner: 1.5m (4.92ft) · Cradle: 1.2m (3.94ft)
Sealing	Scanner: IP52

CERTIFICATES

Certificates & Protection	FCC Part15 Class B, CE EMC Class B, RoHS
---------------------------	--

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland.

**Test conditions: Scan Distance=(min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp; 2D: QR code (15mil) 10 Bytes.

Specifications are subject to change without notice. Version: V1.1