





## P-touch 900 Series

On-demand Labeling for Demanding Work.

**Product SKUs** 

PT-P950NW

PT-P900WC

PT-P900C





P-TOUCH 900 SERIES

# Feature-packed, versatile, and powerful solutions.

These small footprint printers produce wide, premium quality laminated labels at a high print resolution in a variety of sizes and label colors. Making serialized, barcode, or custom labels is easy with the included P-touch Editor Label Design Software and the Pro Label Tool mobile app.

The P-touch 900 Series printers offer a complete on-demand labeling solution for applications that require reliable and quality labels that work on a variety of surfaces and within many harsh and industrial environments.



	Resolution	Speeds	USB	Wi-Fi	Network Capable	Bluetooth (Optional)	Battery (Optional)	Touch Panel & Display (Optional)
PT-P900C	360dpi	2.4 ips max	<b>✓</b>				<b>✓</b>	
PT-P900WC	360dpi	2.4 ips max	<b>✓</b>	<b>~</b>			<b>✓</b>	
PT-P950NW	360dpi	2.4 ips max	~	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>

## **Key features**



**Durable:** Easily create high-quality laminated labels up to 36mm that can hold up to sunlight, UV, extreme temperatures, and other harsh environments.



**Reliable:** Print with confidence knowing you're backed by our industry-leading 2-year Limited Warranty that includes the print head and cutter and at your side support for the life of the product.



**Efficient:** Designed with industrial labeling in mind, help save time, hassle, and clean up with automatic dual blade with half cut feature.



**Compact:** Choose from a range of space-saving desktop printers that give you full functionality in a small footprint.



**Versatile:** Design custom labels - including QR codes and barcodes - by downloading free P-touch Editor software or Pro Label Tool mobile app.



**Connected:** From easy USB connectivity to full network capability to Wi-Fi® to optional Bluetooth® wireless technology, enjoy connectivity that lets you connect and print with ease.





## **Industry applications**

Rely on long-lasting industrial labels for everything from low voltage and electrical labeling to MRO asset management to streamlining your manufacturing and warehousing workflows.



#### Low Voltage/Electrical

- Wire/cable wraps
- Wire/cable flag labels
- Patch panel labeling
- Fiber cable labels
- Electrical boxes & panels
- Equipment, cabinet
   & server rack labels
- Sequentially numbered connections
- Active/passive electronics labels

#### **MRO**

- Asset management labels
- Tools/parts identification
- Barcode labels
- Calibration labels
- Maintenance last performed labels
- Lockout/tagout labels

#### Manufacturing/ Warehouse

- Part labels
- Barcode labels
- Serial number labels
- Part number labels
- Asset management labels
- Parts, bin, & shelf identification
- Component labels
- Shelf and rack labels



#### **Tapes**

Use with TZe and HGe tapes up to 36mm (1.4in) for resistance to chemicals, UV, and abrasions. Also compatible with FLe, HSe and TZeSL cartridges.



#### **Accessories**

Build the printer you want with optional accessories like the Li-on rechargeable battery, Bluetooth® wireless connectivity, and a user-friendly touch panel with display.

#### Get in touch

800-543-6144 MobileSales@Brother.com BrotherMobileSolutions.com

### Software tools for easy integration and label design



P-touch Editor Design Software



Pro Label Tool

	PT-P900C / PT-P900WC	PT-P950NW		PT-P900C / PT-P900WC	PT-P950NW		
General			Printing				
Box Contents	Printer, 36mm x 8m Standar		Print Technology Laminated Thermal Transfer				
AC Adapter (AD9100ESA), AC Power Cord, USB Cable  Dimensions (W x H x D)  AC Adapter (AD9100ESA), AC Power Cord, USB Cable  (W x H x D)  (118mm x 146mm x 192mm)			Print Head Resolution	360dpi x 360dpi			
Weight  3.3lbs (1480g) without tape cassette, battery base and batteries			Print Engine Speed <sup>2</sup>	Up to 2.3ips (60mm/sec)			
Power Specifications	AC adapter (AD9100ESA): 2		Media Type	HGe & TZe Tapes, HSe Heat Shrink Tube, FLe Die Cut, TZeSL Self Laminating Label Cartridges			
Duintou Montou	Battery (Optional): Li-ion Bat Download: Up to 99 Temple	,	Media/Print Width 3.5mm to 36mm				
Printer Memory	(up to 7MB)		Resident Fonts	Helsinki, Letter Gothic, Brussels			
Control panel	PT-P900C: 3 LEDs with 2 keys PT-P900WC: 4 LEDs with 3 keys	4 LEDs with 3 keys	Linear - Code39, Code128, ITF, UPC-A/E, EAN-8/13, GS1-128 (UCC/EAN-128), GS1 DataBar (RSS), Codal Postnet 2D - PDF417, QR Code, Data Matrix, Maxicode, Azte		GS1 DataBar (RSS), Codabar,		
	PT-P900C: Windows® 11, Windows 10 (32bit and 64bit), Windows 8.1	Windows 11, Windows 10 (32bit and 64bit), Windows 8.1 (32bit and	Graphics	Code  Compatible Image Formats (BMP, DIB, JPG/JPEG, TIFF,			
	(32bit and 64bit)	64bit), Windows 8 (32bit		GIF, PNG, WMF, EMF, ICO)			
	PTP900WC: Windows 11, Windows 10 (32bit and 64bit), Windows 8.1 (32bit and 64bit); Windows Server 2022, Windows Server 2019, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012; Mac macOS 10.15.x - 13; Linux Debian and Red Hat LPR and CUPS; Android™ version 9 or later; iOS	and 64bit), Windows 7 (32bit and 64bit), Windows Vista (32bit and 64bit); Windows Server 2022, Windows Server 2019, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012, Windows Server 2012, Windows Server 2008 R2, Windows Server 2008 (32bit and 64bit); Mac OS X 10.9.x - 10.11.x, macOS 10.12.x	Connectivity				
Operating Systems			Communications interfaces	PT-P900C: USB v2.0, RS232C Serial PTP-900WC: USB v2.0, RS232C Serial, Wi-Fi® WLAN 802.11b/g/n (Infrastructure), 802.11n (Wireless Direct)	USB v2.0, RS232C Serial, Wi-Fi WLAN 802.11b/g/n (Infrastructure), 802.11b (Ad-hoc), 802.11n (Wireless Direct), Ethernet 10BASE- T/100BASE-TX Optional: Bluetooth Ver.2.1+EDR (Class 1)		
	version 14 or later  - 13; Linux Debian and Red Hat LPR and CUPS; Android version 9 or later; iOS version 14 or later  Windows: P-touch Editor (with Cable Labeling Wizard), Cable Label Tool, Transfer Manager, Printer Setting Tool, BRAdmin Professional  Mac: P-touch Editor (available Apple App Store), Printer		WLAN Security (Except PT-P900C)	PT-P900WC: WEP, WPA-PSK/WPA2-PSK/ WPA3-SAE (TKIP+AES), WPA3-SAE (AES), EAP- FAST (TKIP/AES), PEAP (TKIP/AES), EAP-TTLS (TKIP/AES), EAP-TLS (TKIP/AES)	WEP, WPA-PSK/WPA2- PSK, LEAP, EAP-FAST (TKIP/AES), PEAP (TKIP/ AES), EAP-TTLS (TKIP/ AES), EAP-TLS (TKIP/AES)		
Included Applications*	Setting Tool PT-P900WC/PT-P950NW o iOS: Pro Label Tool (available) Android: Pro Label Tool (available)	nly: le Apple App Store)	LAN IPv4 Protocols (Except PT-P900C)	ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), mDNS, WINS, Net BIOS name Resolution, DNS Resolver, LPR/LPD, Custom Raw Port/Port9100, FTP Server, TFTP client and server, SNTP client, ICMP, LLMNR			
Cutter	Automatic Dual Blade Cutte (Full and Easy to Peel Strip		I AN IDu6 Protocols	responder, SNMPv1/v2c  NDP, RA, DNS Resolver, LPR/LPD, mDNS, Custom Raw			
Optional Accessories	Battery Base, Li-ion Rechargeable Battery Bluetooth Module, Touch Panel and Display Unit		LAN IPv6 Protocols (Except PT-P900C)  Port/Port9100, FTP Server, SNMPv1, TFTP client and server, ICMP, LLMNR responder, SNMPv1/v2c  *Free download and wireless connection required. Compatibility may vary by device				
Operating temperature / humidity	50° F to 95° F (10° C to 35 condensing		and operating system.				
Warranty	2-year Limited Warranty (in	cludes printhead and cutter)					
Energy Star Qualified (Except PT-P900C)							

Images are for illustrative purposes only. Actual output (such as font and margins) may vary. All specifications subject to change without notice.