

# SLPT Antennas for Public Safety, WLAN, 3G/4G LTE Applications

## Low Profile Transit Style Antennas – Now Available in White and Black

Pulse/Larsen is proud to offer the SLPT (Shadow Low Profile Transit) product line for Public Safety, WLAN, LTE and 3G/4G applications. These rugged, aesthetically pleasing antennas provide a smaller, slimmer option to our LPT product line without sacrificing mechanical or electrical performance. The product line includes both NMO and tamper-proof direct mount products, which support multiple cable and connector options.

SLPT antennas were designed to perform over the high-percentage bandwidth applications prevalent in today's market. These antennas were created specifically to serve emerging Internet of Things applications including 700 MHz Public Safety, LTE, Smart Grid and WLAN. These value-oriented antennas provide a cost-effective, high-performance solution for LTE and 802.11 MIMO applications as well.

Frequency [MHz]	Gain [dBi]	Mounting Style	Part Number Black	Part Number White
698 - 960	4.5	NMO	SLPT698/960NMO	SLPT698/960NMOW
2400 - 2500	4.3	NMOHF	SLPT2400NMOHF *	SLPT2400NMOHFW *
4900 - 5900	5.5	NMOHF	SLPT4900NMOHF *	SLPT4900NMOHFW *
698 - 960 1710 - 2170 2400 - 2700	4.5 5.6 4	NMOHF	SLPT698/2170NMOHF *	SLPT698/2170NMOHFW *
2400 - 2500 4900 - 5900	4.3 5.5	NMOHF	SLPT2400/5900NMOHF *	SLPT245NMOHFW *
698 - 869	4.5	Direct 3/4" Hole 0.905" (23 mm) stud	SLPT698/869DMN	SLPT698/869DMNW
806 - 960	4.5	Direct 3/4" Hole 0.905" (23 mm) stud	SLPT806DMN	SLPT806DMNW
2400 - 2500	4.3	Direct 3/4" Hole 0.905" (23 mm) stud	SLPT2400DMN	SLPT2400DMNW
4900 - 5900	5.5	Direct 3/4" Hole 0.905" (23 mm) stud	SLPT4900DMN	SLPT4900DMNW
698 - 960 1710 - 2170 2400 - 2700	4.5 5.6 4	Direct 3/4" Hole 0.905" (23 mm) stud	SLPT698/2170DMN	SLPT698/2170DMNW
2400 - 2500 4900 - 5900	4.3 5.5	Direct 3/4" Hole 0.905" (23 mm) stud	SLPT2400/5900DMN	SLPT2400/5900DMNW

NMO Mount  
White



Direct Mount  
Black



\* Requires an NMOHF (high frequency) mount

# SLPT Antennas for Public Safety, WLAN, 3G/4G LTE Applications



## Mounting Options



### NMOHF Mounts



SLPT NMO mount (SLPTNMO) antennas are designed to mate perfectly with the Pulse/Larsen NMOHF (high frequency) mount. The NMOHF mount easily converts from low to high frequency applications and back simply by pulling or replacing the center pin and insulator. The larger center contact pin provides for additional strength against downward compression during low frequency installations, resulting in better low frequency VSWR.

For optimal frequency matching, the high frequency and multi band SLPT antennas are designed with an industry-unique coax-type connection which plugs into the Pulse/Larsen NMOHF mount in its high-frequency configuration (i.e. center pin and insulator removed).

NMOHF mounts are available with a variety of cable and connector options. There is also a thick mount version for surface applications up to 1/2" thickness using a standard 3/4" hole. The NMOHF mount is also available in a magnetic mount (NMOMMR) and a mirror bracket (NMOKHFMB).

<p>If your antenna has a "pin" connector, use the NMOHF mount in the low frequency configuration - leave the center pin and insulator in place as it arrives from the factory.</p> <p>"Pin" connector</p> 	<p>If your antenna has a "high frequency" (HF) connector, use the NMOHF mount in the high frequency configuration - remove the center pin and insulator.</p> <p>"HF" connector</p> 
---	---

### NMOHFGPS Mounts

SLPT NMO mount (SLPTNMO) antennas were designed as an ideal match to the NMOHFGPS series mounts. Installing an SLPTNMO antenna on the NMOHFGPS combines the high performance of a GPS antenna with durability of an SLPTNMO antenna. The NMOHFGPS is a direct mount solution utilizing any existing 3/4" hole. This alleviates the need to drill a new hole for mounting.



### Direct Mounts

SLPT direct mount (SLPTDMN) antennas require a 3/4" hole in the mounting surface. SLPTDMN antennas provide a tamper proof solution for applications such as M2M and Public Safety.

**Worldwide Headquarters**  
12220 World Trade Drive  
San Diego, CA 92128  
USA  
Tel 858 674 8100  
Fax 858 674 8262

**Larsen Brand Antennas**  
3611 NE 112th Avenue  
Vancouver, WA 98682  
USA  
Tel 360 944 7551  
800-268 3662 (USA)  
360 891-0057  
800 525 6749 (USA)

**European Headquarters**  
Pulse GmbH & Co. KG  
Zeppelinstrasse 15  
Herrenberg  
Germany  
Tel +49 7032 7806 0  
Fax +49 7032 7806 12

**Asian Headquarters**  
B402, Shenzhen Academy of  
Aerospace Tech Bldg  
Tech-Innovation Internat'l  
10th Kejinan Road  
High Tech Zone  
Nanshan District, Shenzhen  
PR China  
Tel 86 755 33966678  
Fax 86 755 33966700

**Pulse North Asia**  
3E, No. 198, Zhongyuan Rd  
Zhongli City (32068)  
Taoyuan Hsien  
Taiwan (R.O.C.)  
Tel 886 3 4356768  
Fax 886 3 4356823

**Pulse (Suzhou) Wireless  
Products Co, Ltd**  
#99 Huo Ju Road  
(#29 Bldg, 4th Phase)  
Suzhou New District  
Science & Tech Industrial Park  
Jiangsu Province  
Suzhou 215009 PR China  
Tel 86 512 6807 9998  
Fax 86 512 6809 8023