



AR12106CHSSL



Sample photo

Order symbol: AR12106CHSSL
Product nbr: 8561029
Description: PC Enclosure
Remarks: Hinged opaque cover w/S.S. Lockable latch

EAN: 6418074066794
El. number:
Finland:

Including: Hinged cover base with 10-32 brass inserts, latched cover with formed in place PUR gasket, and stainless hinge pin. Quick release latches. (Latch options available.) Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

Dimensions: Length Width Height

mm:	305	254	152
inch:	12.0	10.0	6.0

Materials:

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover screws material:	Stainless steel
Cover colour:	RAL 7035 -light grey
Gasket material:	Polyurethane

Temperatures:

Temperature °C (short term):	-40 ... 140 °C
Temperature °C (continuous):	-40 ... 80 °C
Temperature °F (short term):	-40 ... 284 °F
Temperature °F (continuous):	-40 ... 175 °F

Accessories:

ABP1210	Painted Steel Back Panel
---------	--------------------------

Accessories:

ALBP1210	Aluminum Back Panel
ADFP1210	Dead Front Panel w/ screws
ASP1210	Aluminum Swing Panel
ASPK1210	Swing Panel Kit incl. Panel
ASPHK12	Swing Panel Kit w/o Panel
AMFL10	10" Mounting Flange Set

Rating:

Ingress Protection (EN 60529): IP66/IP67
 Impact Resistance (EN 62262): IK07/IK08
 Electrical insulation: Totally insulated
 Halogen free (DIN/VDE 0472, Part 815): 1
 UV resistance: UL 508
 Flammability Rating: UL 508
 Glow Wire Test (IEC 695-2-1) °C: 960
 NEMA Class: NEMA 4, 4X, 6, 6P, 12, 13

