RuggedJet® 2 Series

2 Inch Receipt & Label Mobile Printer



Compact. Rugged. Connected.

Fast, compact, rugged and ready to connect to virtually any device. RuggedJet 2 series raises the bar in mobile printing performance, ruggedness, operating system compatibility and total cost of ownership

- Fast. Prints at 6 inches per second
- Rugged. IP54 certified, 8.2 foot drop tested, and tumble tested for long-term durability
- Versatile. Compatible with Android[™], iOS[®], and Windows[®] and available with dual wireless radio for Bluetooth[®] or WiFi support
- Advanced. First in 2" class to be Apple
 AirPrint® compatible and new REMOTE
 UPDATE feature to automatically update printer
 settings while in the field and actively in use
- Reliable. Covered by the Brother Assure outstanding two-year Premier warranty





Retail





Transportation



Route Accounting



Pest Management



Field Services



Mobile Professional



Public Safety











Roll Width Roll Width Fixed Wall 2.16* [55mm] or 2.28* [58mm] Must remove insert for wider width Memory 32MB RAM; 32MB RAM; 32MB Islash [12MB Available] USB Inerface USB Ver. 2.0 [full speed], mini B. No USB Host Bluetooth Bluetooth No Yes No Bluetooth2.1 + EDR No Wireless LAN IEEE802.11b/g/n [Infrastructure mode and Adhoc mode: [b/g/n]. Wireless direct mode: [g/n/n]. WLAN N/A Wireless LAN IEEE802.11b/g/n [Infrastructure mode and Adhoc mode: [b/g/n]. Wireless direct mode: [g/n/n]. WLAN Security N/A Infrastructure Mode: Open system (None/WEP) Infrastructure Mode: Open system (Non	Model	RJ-2030	RJ-2050	RJ-2140	RJ-2150
Maximum Print Speed Caps (152 mm/sec)	Print Technology	Direct Thermal			
Type of Brother Media Supported Receipt, Lobel, and Tog (Lobels and Togs require a black mark) Receipt, Lobel, Tog Lobel User Interface 1 ESp.;3 double function buttons, Monocrhom LCD 2.4"/320x120 dat with book light Dimension (WAHxD) 122 mm (4.8" W x 57 mm (2.2" H x 100 mm (3.9")L 150 mm (5.9" W x 73 mm (2.8" H x 100 mm (3.9")L Weight 3.55g (0.78 lbs.) without bottery 4.55g (1.20 lbs) with bottery Print Width (Max) 54 mm Print Width (Max) 54 mm Print Width (Max) 40 mm (1.57") 60 mm (2.3d") Boll Width Fixed Wall 2.16" (55mm) or 2.28" (58mm) Adjustable 1.0" (25mm) to 2.28" (58mm) Memory 322MB RAM; 32MB Flosh (12MB Available) USE Interface USS Ver. 2.0 (full speed), mini B. No USB Host Blueboth Blueboth2.1 + EDR No Blueboth2.1 + EDR MFill Blueboth1 No Yes No Yes WLAN N/A Vireless LAN IEEES02.1 1b/g/n [finitrativeurs and a Adhoc mode: [b/g/n]) / Wireless direct mode: [g/n]) WHAN Socurity N/A Infrestructure Mode: Open system [None/WEF64/WEF64/WEF68] × g. EAP ITS [KRF/AES]. EAP ITS [KRF/A	Print Resolution	203 dpi			
Supported Sec. P. Lobe, and log Cade and log Require o Brock many Sec. P. Lobe, and log Cade and log Require o Brock many	Maximum Print Speed	6 ips (152 mm/sec)			
Dimension (Wx+bdb) 122 mm (4 8") W x 57 mm (2 2") H x 100 mm (3.9") L 150 mm (5.9") W x 73 mm (2.8") H x 100 mm (3.9") L		Receipt, Label, and Tag (Labels and tags require a black mark) Receipt, Label, Tag Label			
Weight 355g [0.78 lbs, without bottery 465g [1.02 lbs] with bottery 545g [1.20 lbs] with bottery 545g [User Interface	1 LED; 3 double function buttons, Monocrhom LCD 2.4"/320x120 dot with back light			
Print Width (Max) Print Width (Max) S4 mm S74 mm S74 mm (2.36*) Roll Diameter (Max) Roll Width Fixed Wall 2.16*(55mm) or 2.28*(58mm) Must remove insent for wider width Memory USB Interface Bluetooth Bluetooth 2.1+EDR MFI (Bluetooth) No Yes WLAN N/A Infrastructure Mode: Open system (None/WEP64/WEP128), Common key authentication (WEP), WPA/WPA2PS (TKP/AES), IEAP (TKP/AES), IEAP (TKP/AES), IEAP STIRE/PAES) Tricels Stirred Mode: WPA2PSK (AES) Prop Protection Secling Certification Peroting Temperatures Operator: 10° to 50°C (with charge: 0° to 40° C) Special Command Language Raster, ESC/P, Plouch Template, ZPUI emulation, CPCL emulation Longuage Barcode Symbologies Rechargeable Lina better, 24th (15 wine) to charging (50/60ta); certer for formic of the right of the r	Dimension (WxHxD)	122 mm $(4.8")$ W x 57 mm $(2.2")$ H x 100 mm $(3.9")$ L 150 mm $(5.9")$ W x 73 mm $(2.8")$ H x 100 mm $(3.9")$ L			
Print Length (Min/Max) Roll Diameter (Max) Adomm [1.57") Roll Width Fixed Wall 2.16" (55mm) or 2.28" (58mm) Must remove insert for wider width insert in insert in its No USB Host Must remove insert for wider width insert in its No USB Host Must remove in i	Weight				
Roll Width Roll Width Fixed Wall 2.16" (55mm) or 2.28" (58mm) Must remove insert for wider width in 8 No USB Host Must remove insert for wider width in 8 No USB Host Must remove insert for wider width in 8 No USB Host Must remove insert for wider width in 8 No USB Host Must remove insert for wider width in 8 No USB Host Must remove in 8 No No Yes Must remove (EKP), / Afford / Writeless inter mode and Adhoc mode: [g/n] Infrastructure Mode: Open system (None/WEP) (Infrastructure mode and Adhoc mode: [g/n] / Writeless inter mode [g/n] Must remove (Infrastructure Mode: Open system (None/WEP) (Paper) (None/WEP) (Infrastructure Mode: Open system (None/WEP) (Infrastructure mode and Adhoc mode: [g/n] Drop Protection 2.5m Multiple drop (under controlled test environment) Secling Certification [P54 without case Operate: -10° to 50° (with charge: 0° to 40° C) Apported Printer Driver Microsoff*, Windows* Visto*, Windows* 8 Windows* 8.1 / Windows* 8.1 / Windows* 9.1 / Wind	Print Width (Max)	54 mm			
Roll Width Fixed Woll 2.16" [55mm] or 2.28" [58mm] Must remove insert for wider width 32MB RAM; 32MB Flash (12MB Available) USB Interface USB Ver. 2.0 (full speed), mini B. No USB Host Bluetooth Bluetooth2.1+EDR No Bluetooth3.1+EDR No Yes No Yes WLAN N/A Wireless LAN IEEEB02.11b/g/n [Infrastructure mode and Adhoc mode: [b/g/n] / Wireless direct mode: [g/n]] WLAN Security N/A Infrastructure Mode: Open system (None/WEP) WEPA-ZPS (TKIP/AES), EAP-TIS (TKIP/AES), EAP-TIS (TKIP/AES), EAP-TIS (TKIP/AES), Wireless Direct Mode: WPA-ZPS (AES) Wireless Direct Mode: WPA-ZPS (AES) Drop Protection 2.5m Multiple drop (under controlled test environment) Sealing Certification IP54 without case Operate: -10° to 50°C (with charge: 0° to 40° C) Specific Temperatures Operate: -10° to 50°C (with charge: 0° to 40° C) Specific Temperatures Operate: -10° to 50°C (with charge: 0° to 40° C) Specific Temperatures Operate: -10° to 50°C (with charge: 0° to 40° C) Supported Printer Driver Microsoff*, Windows* Vista*, Windows* 7 / Windows* 8 Windows* 8.1 / Windows* 10 Supported Command Language Raster, ESC/P, PTouch Template, ZPUII emulation, CPCL emulation CODE39; ITF[12/5]; EAN-13; EAN-8, UPC-A; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNE; UPC-/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); POF417 (Stendard, Truncate, Macroport-ATI); Dear Macrinic Code (model 1, model 2, micro QR); POF417 (Stendard, Truncate, Macroport-ATI); Dear Macrinic Code (model 1, model 2, micro QR); POF417 (Stendard, Truncate, Macroport-ATI); DPC-/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); POF417 (S	Print Length (Min/Max)	12.7 mm; 1 m		nm; 1 m	
Memory 32MB RAM; 32MB Flash (12MB Available) USB Interface USB Ver. 2.0 (full speed), mini B. No USB Host Bluetooth Bluetooth2.1+EDR No Bluetooth2.1+EDR MFi (Bluetooth) No Yes No Yes WLAN N/A Vireless IAN IEEE802.11b/g/n (Infrastructure mode and Adhoc mode: [b/g/n] / Wireless direct mode: [g/n]) WLAN Security N/A Infrastructure Mode: Open system (None/WEP64/WEP12B), Common key authentication (WEP), WPA/WPA2-PS WIAN Security N/A Infrastructure Mode: Open system (None/WEP64/WEP12B), Common key authentication (WEP), WPA/WPA2-PS (KIRP/AES), EAP-TIS (TKIP/AES), EA	Roll Diameter (Max)	40mm (1.57")		60mm (2.36")	
USB Interface	Roll Width			Adjustable 1.0"(25mm) to 2.28"(58mm)	
Bluetooth Bluetooth2.1+EDR No Bluetooth2.1+EDR MFi (Bluetooth) No Yes No Yes WLAN N/A Wireless LAN IEEE802.11b/g/n [Infrastructure mode and Adhoc mode: [b/g/n] / Wireless direct mode: [g/n]] AdHoc Mode: Open system [None/WEP] Infrastructure Mode: Open system [None/WEP] / [None/WEP4/WEP128], Common key authentication WEP1, WPA/WPA2-P5 [TKIP/AE5], LEAP [CKIP], EAPFAST, TKIP/AE5], EAP TKIP/AE5], Sa, EAP-TILS [TKIP/AE5], EAP-TILS [TKI	Memory	32MB RAM; 32MB Flash (12MB Available)			
MFi (Bluetooth) No Yes No Yes No Yes No Yes Wireless LAN IEEE802.1 lb/g/n (Infrastructure mode and Adhoc mode: [b/g/n] / Wireless direct mode:[g/n]] AdHoc Mode: Open system (None/WEP) AdHoc Mode: Open system (None/WEP) Infrastructure Mode: Open system (None/WEP4) (IKIP/AES), Cemmon key authentication (WEP), WPA/WPA2-PS (IKIP/AES), PEAP [IKIP/AES], PEAP [IKIP/AES], PEAP [IKIP/AES], PEAP IKIR/AES], PEAP IKIR/AES], PEAP IKIR/AES], PEAP IKIR/AES], PEAP IKIR/AES] Drop Protection 2.5m Multiple drop (under controlled test environment) Sealing Certification IP54 without case Operatie: -10° to 50°C (with charge: 0° to 40° C) Addition of the controlled test environment) Sealing Certification IP54 without case Operatie: -10° to 50°C (with charge: 0° to 40° C) Addition of the controlled test environment) Soby Android™ 4.0.3 or later; iOS° 6 and above; Windows® 8.1 / Windows® 10 SDK Android™ 4.0.3 or later; iOS° 6 and above; Windows® Mobile Supported Command Language Raster, ESC/P, P.Touch Template, ZPUII emulation, CPCL emulation CODE39; ITF(I+2/5); EAN-13; EAN-8; UPC-4; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Reatangular); MaxiCode; Aztec Ascording Control (Control of the Control of Cothic, Letter Gothic Bold, Helsinki Max: 400dot; According 150/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging (50/60Hz);	USB Interface	USB Ver. 2.0 (full speed), mini B. No USB Host			
WLAN N/A Wireless LAN IEEE802.11 b/g/n [Infrastructure mode and Adhoc mode: [b/g/n] / Wireless direct mode: [g/n]) WLAN Security N/A Infrastructure Mode: Open system (None/WEP64/WEP128), Common key authentication (WEP), WPA/WPA2-PS [TKIP/AES], LEAP (CKIP), EAP-FAST (TKIP/AES), PEAP (TKIP/AES), PEAP TKIF/AES), EAP-TILS (TKIP/AES), EAP-TILS (TKIP/AES), Wireless Direct Mode: WPA2-PSK (AES) Drop Protection 2.5m Multiple drop (under controlled test environment) Sealing Certification IP54 without case Operating Temperatures Operate: -10° to 50°C (with charge: 0° to 40° C) upported Printer Driver Microsoff®, Windows® Vista®, Windows® 7 / Windows® 8.1 / Windows® 10 SDK Adroid™ 4.0.3 or later; iOS® 6 and above; Windows® Mobile Supported Command Longuage Raster, ESC/P, P-Touch Template, ZPLII emulation, CPCL emulation CODE39; ITF(I-2/5); EAN-13; EAN-8; UPC-8; UPC-8; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNET, UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec **ESC/P*, Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size-16, 24, 32dot>; Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot, <p-touch® (12="" (15="" (50="" (battery="" 60hz);="" 7.2vdc;="" ac="" adapter="" battery:="" car="" charger)="" charging="" charging<="" cigarette="" for="" li-ion="" only="" or="" rechargeable="" td="" templates="" type="" v)="" vdc)="" veer="" wired=""><td>Bluetooth</td><td colspan="2">Bluetooth2.1+EDR</td><td>No</td><td>Bluetooth2.1+EDR</td></p-touch®>	Bluetooth	Bluetooth2.1+EDR		No	Bluetooth2.1+EDR
MLAN Security N/A (b/g/n) / Wireless direct mode: [g/n]) AdHoc Mode: Open system (None/WEP) Infrastructure Mode: Open system (None/WEP) Infrastructure Mode: Open system (None/WEP28), Common key authentication (WEP), WPA/WPA2-PS (IKIP+AES), LEAP (CKIP), EAP-FAST (IKIP/AES), EAP-ITIS (IKIP/AES), EAP-ITIS (IKIP/AES) Wireless Direct Mode: WPA2-PSK (AES) Drop Protection	MFi (Bluetooth)	No	Yes	No	Yes
MIAN Security N/A Infrastructure Mode: Open system (None/WEP64/WEP128), Common key authentication (WEP), WPA/WPA2-PS (TKIP/AES), EAP (CKIP), EAP-FAST (TKIP/AES), PEAP (TKIP/AES), *3, EAP-TILS (TKIP/AES), Wireless Direct Mode: WPA2-PSK (AES) Drop Protection 1P54 without case 1P54 without case Operate: -10° to 50°C (with charge: 0° to 40° C) Supported Printer Driver Microsoff®, Windows® Vista®, Windows® 7 / Windows® 8.1 / Windows® 10 SDK Android™ 4.0.3 or later; iOS® 6 and above; Windows® Mobile Supported Command Language Raster, ESC/P, P-Touch Template, ZPLII emulation, CPCL emulation CODE39; ITF(I-2/5); EAN-13; EAN-8; UPC-A; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix/ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec **ESC/P*; Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size<16, 24, 32dot>; Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot; <p-touch® template=""> **Ver (Battery / Charger) Rechargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging</p-touch®>	WLAN	N/A	Wireless LAN		Adhoc mode:
Sealing Certification IP54 without case Operate: -10° to 50°C (with charge: 0° to 40° C) Upported Printer Driver Microsoft®, Windows® Vista®, Windows® 7 / Windows® 8. Windows® 8.1 / Windows® 10 SDK Android™ 4.0.3 or later; iOS® 6 and above; Windows® Mobile Supported Command Language Raster, ESC/P, P-Touch Template, ZPLII emulation, CPCL emulation CODE39; ITF(I-2/5); EAN-13; EAN-8; UPC-A; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec Internal Fonts and Sizes Ver (Battery / Charger) Rechargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging	WLAN Security	N/A		None/WEP64/WEP128), Common key aut T (TKIP/AES), PEAP (TKIP/AES) *3, EAP-TLS	
Android™ 4.0.3 or later; iOS® 6 and above; Windows® Mobile SUPPORTED COMMAND SDK Android™ 4.0.3 or later; iOS® 6 and above; Windows® Mobile Supported Command Language Raster, ESC/P, P-Touch Template, ZPLII emulation, CPCL emulation CODE39; ITF(I-2/5); EAN-13; EAN-8; UPC-A; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec **ESC/P>; Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size<16, 24, 32dot>; Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot; <p-touch® template=""> **Ver (Battery / Charger) Rechargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging</p-touch®>	Drop Protection	2.5m Multiple drop (under controlled test environment)			
pupported Printer Driver Microsoft®, Windows® Vista®, Windows® 7 / Windows® 8.1 / Windows® 10 SDK Android™ 4.0.3 or later; iOS® 6 and above; Windows® Mobile Supported Command Language Raster, ESC/P, P-Touch Template, ZPLII emulation, CPCL emulation CODE39; ITF(I+2/5); EAN-13; EAN-8; UPC-A; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec **ESC/P**; Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size<16, 24, 32dot>; Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot; <p-touch® template=""> **Ver (Battery / Charger) Rechargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging</p-touch®>	Sealing Certification	IP54 without case			
SDK Android™ 4.0.3 or later; iOS® 6 and above; Windows® Mobile Raster, ESC/P, P-Touch Template, ZPLII emulation, CPCL emulation CODE39; ITF(I+2/5); EAN-13; EAN-8; UPC-A; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec **ESC/P**, Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size<16, 24, 32dot>; Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot; <p-touch® template=""> **Ver (Battery / Charger) Rechargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging</p-touch®>	Operating Temperatures	Operate: -10° to 50°C (with charge: 0° to 40° C)			
Raster, ESC/P, P-Touch Template, ZPLII emulation, CPCL emulation CODE39; ITF(I-2/5); EAN-13; EAN-8; UPC-A; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbologies RSS symbologies RSS symbologies PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec **ESC/P-*; Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size<16, 24, 32dot>; Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot; <p-touch® template=""> **Ver (Battery / Charger) Rechargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging</p-touch®>	upported Printer Driver	Microsoft®, Windows® Vista®, Windows® 7 / Windows® 8 Windows® 8.1 / Windows® 10			
Language CODE39; ITF(I-2/5); EAN-13; EAN-8; UPC-A; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec **ESC/P>; Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size<16, 24, 32dot>; Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot; <p-touch® template=""> **Rechargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging</p-touch®>	SDK	Android™ 4.0.3 or later; iOS® 6 and above; Windows® Mobile			
RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec **Reshargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging	• •	Raster, ESC/P, P-Touch Template, ZPLII emulation, CPCL emulation			
ver (Battery / Charger) Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot; <p-touch® template=""> Rechargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging</p-touch®>	Barcode Symbologies	RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR);			
Cigarette car adapter or Wired type (12 VDC) only for charging	nternal Fonts and Sizes				
Package Contents Printer, Belt Clip, Li-ion battery	wer (Battery / Charger)				;
	Package Contents	Printer, Belt Clip, Li-ion battery			

RuggedJet 2 Supplies, Accessories and Service

2-Year Premier Warranty. For extended warranty go to www.BrotherAssureServiceProgram.com



Supplies

Warranty

- Brother Premium receipt paper and label rolls for all your applications.
- Custom options also available.



Accessories

• Optional accessories include extra batteries, shoulder strap, belt clip, DC vehicle adapter, AC charger, battery charger, carrying cases and more.



• Extend the useful life of your printer by adding an extended service program.

800-543-6144 mobilesales@brother.com www.brothermobilesolutions.com at your side