



INDUSTRY-LEADING

Thermal Transfer Printers



TECEX6M

The TECEX6M printers are ideal for tags, labels and signs up to 6" wide at speeds up to 12 ips. Utilizing the End-To-End Slip-On® tags, various pot tags, and pressure sensitive signs makes this the most versatile printer for the money on the market.

TXPEX6

The TXPEX6 printer provides utility above and beyond its price tag at speeds up to 12 ips. This printer can easily handle tag widths up to 10" ladderstyle (sideways). This print orientation promotes faster throughput and maximum ribbon usage. The rugged powder coated industrial strength steel case is designed for harsh environments.

Key Features

- FETHR Head - Floating Edge Type Head
- Fast to Load Label & Ribbon Path
- Print Media Thickness up to 25 mil
- Standard USB and Ethernet
- Fast and Easy Handling
- High Speed Printing
- High Quality Print Technology
- RFID Ready



GENERAL SPECIFICATIONS / HORTICULTURE



Printer Model	TECEX6M		TXPEX6	
PRINTER SPECIFICATIONS				
Printing Method		Thermal Transfer		
Resolution		305 dpi (12 dots/mm)		
Maximum Print Speed		12 ips		
Maximum Print Area		6.29" (160 mm) width		
Print Length		Batch: 0.31 - 58.97" (8 - 1498 mm) Cut: 0.80 - 58.81" (20.4 - 1494 mm) Peel-off: 0.92 - 10" (23.4 - 254 mm)		
MEDIA SPECIFICATIONS				
Media Type		Die cut or continuous, Roll-fed		
Adjustable Sensing		Die cut, black mark, notched, hole punched		
Media Width Range	2 - 6.5" (50 - 140 mm)		2 - 10" (50 -229 mm)	
Media Thickness		5.1 - 25 mil (0.08-0.25 mm)		
Inner Media Core Diameter		1.57 - 3" (40 - 76.2 mm)		
Outer Media Core Diameter		Max 8" (203 mm)		
Ribbon Width		Max 6.7" (170 mm)		
Ribbon Length		1,968 feet (600 m)		
Ribbon Save Mode		Standard		
Ribbon Core and Max diameter		Core 1" (25.4 mm) and Max diameter 3.54" (90 mm)		
MEMORY/PROCESSING				
Main Memory		16 MB (FROM), 32 MB (SRAM)		
INTERFACES				
Standard		USB 2.0, LAN, 10/100 Base, IPv6, USB Host/RTC		
Optional		RS232, Centronics, Wireless LAN, RFID		
Emulation		ZPL II		
Printer Driver		Windows 10/8/7/Vista (32/64 bit), Windows Server 2012/Server 2008 (32/64 bit)		
FONT/BARCODE SYBOLOGIES				
Barcodes		EAN8, EAN13, JAN8, JAN12, UPC-A, UPC-E, NW-7, CODE 39, Code 93, ITF, MSI, Code 128, EAN 128, Industrial, 2 of 5, Customer Barcode, POSTNET, RM4SCC, KIX CODE, GS1 DataBar		
2D Codes		Data Matrix, PDF 417, Maxicode, QR Code, Micro PDF 417, CP Code		
Fonts		Bitmap font, Outline font, Price font, TTF, OFT, Writable characters, Optional True Type		
Language Mode		TPCL, BCI (function)		
OPERATING & ENVIRONMENTAL				
Power supply		AC 100 to 240V, 50/60 Hz		
Operating Temperature / Humidity		5°C to 40°C / 25-85% non-condensing relative humidity (RH)		
Storage Temperature / Humidity		"-40°C to 60°C / 10-90% non-condensing relative humidity (RH)		
Dimensions	13.02" (331 mm) W x 18.11" (460 mm) D x 12.20" (310 mm) H		15.75" (400 mm) W x 18.11" (460 mm) D x 12.20" (310 mm) H	
Printer Weight	44 lbs		58 lbs	
Casing		Powder-coated industrial strength steel		
User interface		Graphic LCD, 2 x Status LED, 10 x key		
OPTIONS				
UHF RFID				

SATO AMERICA CORPORATE

10350-A Nations Ford Rd
Charlotte, NC 28273

Phone: (704) 644-1650

sales-sallc@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com/hort

©2019 SATO America. All rights Reserved. Rev A • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.