



SG112-ex

Print large-format labels at top speed

Applications



KEY FEATURES AND BENEFITS

- 10.5-inch print width for high-resolution large format printing
- Fast and consistent throughput; print speeds up to 6 inches per second
- Increase productivity with multiple labels printed simultaneously
- Automatic label loading
- Intuitive multi-language display
- Flexible connectivity with multiple standard interfaces
- Durable and robust design

GENERAL SPECIFICATIONS / SG112-ex

PRODUCT SPECIFICATIONS			
Print Resolution		305 dpi (12 dots/mm)	
Print Speed		3, 4, 5, 6 ips (75, 100, 125, 150 mm/sec)	
Print Area	Max Width	10.5" (266.7 mm)	
	Max Length	16.5" (420 mm)	
Media Size (with liner)	Width	Continuous / Tear Off / Tray / Cutter	5.2" - 11.8" (131 - 300 mm)
		Continuous	0.35" - 98.43" (9 - 2500 mm)
	Tear Off	0.79" - 98.43" (20 - 2500 mm)	
	Tray	1.7" - 4.7" (43 - 120 mm)	
	Cutter	1.7" - 16.7" (43 - 423 mm)	

PRINTING SPECIFICATIONS

Method

Thermal Transfer and Direct Thermal

Mode

Continuous, Tear-off, Cut & Print (cutter model)

MEDIA SPECIFICATIONS

Sensor Type

I-Mark Sensor (Reflective) / Label Gap Sensor (Transmissive)

Media Type

Roll or fan-fold die cut labels

Media

Thickness (Label & Liner)

0.0031" - 0.0106" (0.08 - 0.27 mm)

*Use media 0.0047" (0.12 mm) or greater in thickness for Auto Feed mode

*Use media 0.0083" (0.21 mm) or lesser in thickness for Cutter option

Roll Diameter

Maximum 8" OD (200 mm) on 3" (76 mm) core

Wind

Face-in / Face-out

Ribbon

Length / Diameter

Maximum 984.25 ft. (300 m) / Maximum 2.76" OD (70.0 mm)

Width

5.7" - 10.7" (145 - 273 mm)

Core Diameter

1.01" ID (25.6 mm)

Wind Direction

Face-in

SATO Genuine Consumables

For maximum print quality and optimum use, SATO recommends the use of SATO genuine consumables

FONT SPECIFICATIONS

Internal Fonts

22 Bitmap Fonts, 8 Scalable Fonts, Multi-language display and printing of Asian fonts

CONNECTIVITY

USB 2.0 (Type A & B), LAN, RS-232C, IEEE1284, EXT, SD Card Slot, USB Type A

MEMORY & PROCESSING

CPU Type

32bit RISC-CPU 250MHz

On-Board Memory

Flash ROM: Standard Memory Size 40MB
User area 4.5 MB

SDRAM: Standard Memory Size 64MB

User Downloadable Fonts, Graphics or Format

Maximum 100 MB

USER FRIENDLY SUPPORT TOOLS

Large Status LED

POWER (Green/Orange), ONLINE (Green), STATUS (Green/Red), LABEL (Red), RIBBON (Red).

Audible Alerts

Adjustable volume setting

Self Diagnosis

Head Open, Ribbon Open, Cutter-cover Open

Display Panel

3.3" LCD display with three color LED (green, orange, red) and brightness adjustment

Operation Buttons

LINE, FEED, FUNCTION, ENTER, CANCEL Arrow buttons

Print Setting Tool

SATO-All-In-One-Tool

Multi-national Language Support

English, Chinese, and Japanese display language options

OPTIONS

RTC (Calendar) Kit, Catch Tray, Unwind Unit.

BARCODE SYBLOGIES

Barcodes

Linear

UPC-A, UPC-E, JAN/EAN, CODE39CODE93, CODE128, GS1-128(UCC/EAN128), ISBT128, CODABAR(NW-7), ITF, Industrial 2of5, Matrix 2of5, MSI, POSTNET, BOOKLAND, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked, Intelligent Mail Barcode (IMb). *GS1 DataBar was formerly called RSS.E

2D Symbolgies

QR Code (including Micro QR) PDF417 (including MicroPDF) MAXICODE (Ver.3.0) GS1 DataMatrix (ECC200 Ver.2.0)

OPERATING CHARACTERISTICS

Electrical Requirements

AC100 V ~ 240 V ±10% (full range) / at 50/60 Hz.

Standards & Agency Approvals

FCC Part 15 Subpart B Class A/ICES-003 Class A, CE(EN55032, EN55024), CCC(GB/T9254-2008, GB17625.1-2012) BSMI(CNS13438), UL 60950-1/CSA C22.2 No.60950-1, CE, Nemko-GS EN60950-1, CCC(GB4943.1-2011), BSMI(CNS14336-1), BIS(IS 13252).

Environment

Operating

41 to 104°F (5 - 40°C), 30 - 80% RH (without condensation)

Storage

23 to 140°F (-5 to 60°C), 30 - 90% RH (without condensation)

PHYSICAL CHARACTERISTICS

Dimensions

18.70" W x 12.34" L x 12.57" H (475 mm x 313.4 mm x 319.2 mm) - 20.30" H (515.5 mm) with cover open.
6.46" (164 mm): Media exit area.
3.35" (85.1 mm): Tray - Cutter Model Only.

Weight

Standard Model (Media/Ribbon excluded):
Approx. 44.1 lbs. (20.0 Kg)
Cutter Model (Media/Ribbon excluded):
Approx. 51 lbs. (23.1 Kg)

MISCELLANEOUS

SNMP enabled, SBPL Command Error Mode, Maintenance notifications, Error indicators, Data save mode

*Available in standard model and cutter model

SATO AMERICA CORPORATE

10350-A Nations Ford Rd
Charlotte, NC 28273

Phone: (704) 644-1650

sales-sallc@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com/SG112ex

©2020 SATO America. All rights Reserved. Rev A • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.



BARCODE
FACTORY

Barcode Factory

A Paragon Print Systems Company

2021 Paragon Drive | Erie PA 16510
814.456.8331 | Toll Free: 888.237.8525
info@barcodefactory.com