



POS Keyboards

K2724 POS Keyboard with MSR

The K2724 POS Keyboard features a **dual track** Magnetic Stripe Reader and built-in bar code scanner port, providing a space-saving, one-piece solution suitable for point of sale, banking and other commerce applications. It provides basic customization through 21 relegendable keys. Rugged construction and a spill resistant design guarantee an extended life cycle.



KP2724 Programmable POS Keyboard with MSR

The KP2724 is the programmable version of the K2724. Its features allow full customization of the unit. It supports 24 macros of up to 32 characters each. Every key can be remapped to change the keyboard's layout. Additionally, 90 keys can be relabeled to your specific needs. This prevents mistakes, reduces the learning cycle and speeds up operations.



K2724 Features

- Compact, space saving design.
- 21 relegendable keys.
- Built-in dual track Magnetic Stripe Reader.
- Integrated bar code decoder accepts wand, laser scanner, CCD, or RS232 input.
- Spill resistant construction.
- Num-Lock, Caps Lock, Scroll Lock, and Good Read LEDs.

KP2724 Features

- Compact, space saving design.
- 24 programmable keys, 32 characters per key.
- 90 relegendable keys.
- 101/102 remappable keys.
- Built-in dual track Magnetic Stripe Reader.
- Integrated bar code decoder accepts wand, laser scanner, CCD, or RS232 input.
- Spill resistant construction.
- Num-Lock, Caps Lock, Scroll Lock, Good Read and Prog. Macro LEDs.

SPECIFICATIONS		
Mode	K2724	KP2724
Layout	104	101
Relegendable keys	21	90
Programmable keys	Non-programmable	24
Remappable keys	N/A	101
Integrated magnetic stripe reader	Track I & II (ISO 7811)	
Built-in bar code decoder	Decoder accepts wand, CCD, laser, or serial input	
Compatibility	IBM AT, PS/2	
Total key travel	4.0 ± 0.3 mm	
Key type	Membrane switch, 20 million strokes life cycle	
Electrical	5V DC ± 5% @ 250 mA	
Environmental	Operating: 32° to 131° F (0° to 55° C)	
	Storage: -4° to 149° F (-20° to 65° C)	
Dimensions	Humidity: 10 to 95% RH (non-condensing)	
	15.8" x 8.3" x 1.7" (400 x 210 x 43 mm)	
Warranty	One year	