unitech

PA968 Mobile Computer



Designed for maximum efficiency and versatility

The Unitech PA968 mobile computer features an ergonomically designed, ultra robust Aluminum-Magnesium alloy housing. Ideally suited for a wide range of applications in any transportation or field service based enterprise, the PA968 offers four fullyintegrated wireless technologies into a versatile multi-functional platform.

Tough enough for even the most adverse environmental conditions

Not only designed for versatility, the PA968 is also constructed for durability with an IP65 rating and 5-foot drop threshold to concrete. Having a strong water and dirt resistant design makes the PA968 suitable for the harshest environments and conditions, minimizing down time and repair costs. Product functionality and reliability are vital performance enhancement features of the PA968.

The powerful and seamlessly integrated wireless platform

The PA968 utilizes state of the art technology in its seamless wireless connectivity. Supported by Windows CE for application customization, the PA968 has built-in GPS with InstantFixTM and 3.5G (including HSDPA) wireless capability. With these networking capabilities, the PA968 is able to track / trace the device and applicants via satellite; and transmit collected data to server in a very short time.

High-end security to avoid losing confidential data

Security is also an important aspect of data collection, thus, the PA968 has a built-in high-resolution finger print reader to confirm user ID authentication and to protect their privacy and important business information. In addition, the PA968 is equipped with a large memory capacity to maximize data storage, thereby eliminating the need for additional memory accessories, to further safeguard against data loss.

The unique benefit of cutting edge design

In today's ever-expanding market place where time, efficiency and accuracy are of utmost importance, the utilization of global communication technology greatly benefits any mobility enterprise. In order to meet these demands, the PA968 offers optional Intelligent Modularized Keypads to meet the needs of various applications. The swappable keypad option enables users to minimize downtime and provides a more convenient and cost-effective solution for special keypad requests. To further address the needs of the modern mobile workforce, the PA968 includes a high sunlight readability LCD for increased screen visibility when working outdoors.

User-friendly functionality and innovative design make the Unitech PA968 the product of choice for reducing operational costs and providing timely delivery and accuracy of data readings, all in one incredibly useful device.

Main Features

- All new, lightweight aluminum-magnesium alloy design
- Optional intelligent modularized keypads
- High sunlight readability, 3.5-inch high resolution touch screen with LED backlight
- Windows CE 5.0 for customized applications
- Built-in GPS system with InstantFixTM support for global access and positioning
- 3.5G wireless capabilities (including HSDPA)
- 802.11b/g (CCX4 certified), Bluetooth 2.0 + EDR
- Linear laser scanner and 2D imager, reads most common bar code symbologies
- IP65 rating, 5-foot drop threshold to concrete
- 2 megapixel color camera with LED flash for clearer images
- 500 dpi finger print scanner designed for ID authentication management
- Large battery capacity, 13.69 Watts, ensures long operating time
- 320MB FlashROM and 128MB RAM for system and user data storage (the largest memory capacity in its class)





unitech

System Specs

CPU
Memory

520MHz Intel PXA270 Processor SDRAM: 128MB Flash ROM: 320MB

Microsoft Windows CE 5.0

OS

Display

240x320 QVGA, Color Transflective TFT, with Touch Screen & backlight

Keypad

Modularized keypad: 24-key keypad in default package, includes numeric keys, alpha keys and function keys

43-key keypad (optional)

Input Device

Keypad, Touch Screen, Full Alphanumeric Software Keyboard, Bar Code Scanner and Finger Print Scanner (optional) 500DPI / 256 gray scale 2.0 Megapixels Camera Flashlight 60 Lux (30cm)

Indicator

LEDs, Vibrator

Symbologies

1D Bar Code Engine

UPC-A/E, EAN-8/13, Codabar, Code 39, Code 39 full ASCI, Code 93,Code 32, Interleaved & Std. 2 of 5, EAN 128, Code 11, Delta, MSI/Plessey, Code 128, Toshiba

2D Imager (optional)

- Australian post, British post, Canadian post, 1D codes Codabar, Code 11, Code 128, Code 39, Code 93, EAN 13, EAN 8, IATA 2 of 5, ITF, ISBT, Japanese post, Kix code (nl), Korean post, Matrix 2 of 5, MSI, Planet code, Postnet, RSS expanded, RSS limited, RSS 14, UPC A, UPC E, UPC E1
- 2D codes Aztec, Codablock F, Code 49, Datamatrix, EAN-UCC, composite, Maxicode, Micro PDF417, PDF 417, QR code, Tcif lonked C39

Audio

MIC, Speaker, Headset Connector, Receiver



Unitech America

Los Angeles, Houston, Guadalajara http://www.ute.com e-mail: inquiry@ute.com http://latin.unitech-adc.com e-mail: info@latin.ute.com

Unitech Asia Pacific & Middle East

Taipei http://www.unitech-utp.com.tw e-mail: aidcsales@tw.ute.com

Unitech Japan Tokyo

http://www.unitech-japan.co.jp e-mail: sales@jp.ute.com

PA968 Specifications

Communication

USB	1.1 Host & Client
WLAN	IEEE 802.11b/g, (CCX4 certified)
PAN	Bluetooth 2.0 EDR
WWAN	3.5G Five-bands, GSM/GPRS 850MHz , 900MHz
	1800MHz and 1900MHz, UMTS WCDMA/HSDPA,
	50MHz, 1900MHz, 2100MHz / GPRS EDGE
GPS	Sirf star III Chip set, Supporting InstantFix [™]

Power Source

Main Battery **Backup Battery Operation Hours** 13.69 Watts Li-ion battery pack One rechargeable Ni-MH backup battery Up to 10 hours, depending on configuration and application

Approximately 199.5mm x 88mm x43.3mm

(Antenna length excluded)

Enclosure

Weight Dimension

Environmental

Operating temperature Storage temperature **Relative Humidity** Drop test to Concrete **Environmental Sealing**

14° F to 122° F (-10°C to 50°C) -4°F to 140°F (-20°C to 60°C) 5% ~ 95% (non-condensing) 5 feet (1.5m) IP65

Software

Microsoft Visual Studio 2005 Microsoft Windows CE 5.0 SDK (from Unitech) Oracle Database Lite

500a

Accessories

Desktop USB Cradle USB communication and charging cable AC adapter (with regional power cord) Vehicle Cradle Battery Charger 4-Slot Multi-Bay Ethernet Cradle

Regulatory Approvals CE, FCC, BSMI, VCCI, CCC, RoHS compliance

Unitech Europe Tilburg / Netherlands http://www.unitech-europe.com e-mail: sales@eu.ute.com

Unitech Greater China Beijing, Shanghai, Guang Zhou, Xiamen http://www.ute.com.cn unitech@cn.ute.com Taipei http://adc-utt.unitech.com.tw barcode@tw.ute.com

Head Office Taipei

http://www.unitech-adc.com e-mail: marketing@tw.ute.com

Specifications subject to change without notice. Copyright 2009 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners