

The Unitech EA500 (Android 7.1) is a rugged 5" mobile enterprise computer combining strong features with powerful data collection. The EA500 provides convenient connectivity, reading capabilities and enhances the service level for a variety of vertical applications within the retail, hospitality and field service sectors.

Compact Design, Rugged Format

Powered by the steady Android 7.1 operation system, EA500 is one of the most flexible mobile computer with a weight at only 210g. It's easy to carry around for a variety of vertical applications within the retail, hospitality and field service sectors.

High Resolution Camera for workforce

Equipped with a 8MP rear camera with autofocus and LED flash and the 5MP front camera , the EA500 is ideal for capturing digital evidence for proof-of-delivery.

1.5M Drop specification

Design to survive in harsh environments, this enterprise mobile computer is rugged enough to drop from the 1.5 meters onto concrete. The EA500 is highly reliability to meet the needs in a wide range of mobile workforce.

IP67 Rugged Protection

Engineered with industrial grade materials, the EA500 is available to survive through the harsh environments with its IP67 waterproof and dustproof rating.

2D Scanning Capability

Featuring superior 1D and 2D barcode reading performance, it ensures read reliability for mobile phone screens and paper in any orientation. The EA500 gives your workforce the technology it needs to take your business to the next level.

Built in NFC RFID Reader/Writer

The EA500 features a NFC reader and writer that allows users to log in the terminal with private identification card.

Equipping with Rugged POGO PIN & USB Type-C

The pogo-pin design protects the handheld from the wear and tear of frequent charging and docking. The EA500 also comes with a USB Type-C for data transforming.

High Capacity 3800mAh Rechargeable Battery

The highlight of the mobile computer is its huge 3800 mAh rechargeable battery, which provides tons of power even with aggressive usage.

Features

- All-in-one function: 2D Imager, HF/NFC and 8MP Camera
- Industrial grade: 1.4GHz Quad-Core processor with Android 7.1 OS
- Suitable for any mobile worker: 3G / 4G LTE, Dual-Band 802.11 a/b/q/n/ac WiFi, GPS and BT 4.1
- Rechargeable 3800mAh battery
- 5" HD display. Ultra sensitive capacitive touch screen (compatible with gloves and supports wet resistance)
- Rugged: Corning® Gorilla Glass® 3, IP67 rated and 5-foot drop specification
- Dual Scanning Buttons (left and right side) and programmable key
- \bullet Device supported versatile: SOTI, 12Manage and MoboLink





EA500Specifications



1

Operation System

CPU 1.4GHz, Qualcomm 8917 Quad core processor

Memory 2GB DDR RAM 16GB ROM

OS Android 7.1

Enhanced security by preventing 3rd party data

collection (without GMS).

Languages Multi-language

Others Input Chinese/ English, supports handwriting

and soft keyboard.

Display

5.0 inch TFT-LCD HD (720 \times 1280) color screen, Gorilla Glass 3. Ultra sensitive capacitive touch screen, compatible with gloves and

supports wet resistance.

Buttons

Side SCAN button x 2 (Left / Right), User-defined function button (programmable key), Volume switch button (+ / -), ON / OFF button.

Camera/Photos/Video

2MP front camera

8MP rear camera with LED flash and auto-focus function

Symbologies

2D Imager

1D/2D All major 1D and 2D codes

RFID

HF/NFC Frequency 13.56Mhz

Support: ISO14443A/B, ISO15693 standard,

Supports NFC

Device supported MDM

SOTI, 12Manage and MoboLink

Regulatory Approvals

CE, RED, NCC, CCC, VCCI, FCC

Communication USB

USB Type C
OTG Yes, over USB Type C

POGO PIN Charging via cradle and USB client

WLAN 802.11 a/b/g/n/ac

Bluetooth BT 4.1, support BR/ EDR + BLE

WWAN EU 4G FDD-LTE(B1, B2, B3, B7, B8, B20, B28A, B28B)

3G UMTS/HSDPA/HSPA/HSPA+ (900, 1900,2100MHz)

US 4G FDD-LTE B1,B2,B4,B7,B5,B20,B28A,B28B

3G UMTS/HSDPA/HSPA/HSPA+ (850,1900, 2100MHz) 2G GSM/EDGE/GPRS(850,1900)

CN 4G FDD LTE B1,B3& TDD B38,39,40,41

3G UMTS/HSDPA/HSPA/HSPA+ (900,2100 MHz) CDMA EV-DO Rev.A (800MHz), Band 34, 39

Sensors Proximity sensor, light sensor and G-sensor

E-compass, gyroscope, and height meter

Audio

Microphone, speaker and 3.5mm audio jack

Expansion Slot

Micro SD/TF x 1(maximum of 32 GB), Micro SIM x 2

Enclosure

Dimension 158 mm x 76.2 mm x 11.5 mm

Weight 210g

Environmental

Operating temperature -10°C to +50°C
Storage temperature -20°C to +70°C
Charging Temperature 0°C to 40°C

Relative Humidity 5% ~ 95% (non-condensing)

Drop Specification 1.5m to concrete

Sealing IP67

Accessories

Single slot USB cradle

Indicator

LEDs, Vibrator

Power Source

Main battery
 Rechargeable and Changeable (Non-swappable)

3.8 V, 3800mAh Polymer Li-ion battery built-in.

Operation time 10-12 hours (depending on the specific environment)

RTC battery Real time clock battery

Warranty

1 Year Terminal and cradle / 3 months battery.

UKAS UKAS WATER



Headquaters

http://www.ute.com e-mail:info@hq.ute.com

unitech America

Los Angeles

http://us.ute.com e-mail: info@us.ute.com

http://can.ute.com info@can.ute.com

Mexico

http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipe

http://mideast.ute.com info@mideast.ute.com

unitech Europe

Tilburg / Netherlands http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan

Tokyo

http://jp.ute.com e-mail:info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com info@cn.ute.com Taipei http://tw.ute.com info@tw.ute.com

