



 DATASHEET

# Brother RuggedJet 4200 Series

Robust mobile printing  
for tough jobs

## Product SKUs

RJ-4230BL

RJ-4250WBL

RJ-4230B

RJ-4250WB



## RUGGEDJET 4200 SERIES

# Built for Real Work.

Designed and engineered based on the real feedback of real customers, the RuggedJet 4200 Series doesn't just raise the bar on performance, ruggedness, and connectivity – it redefines the bar. With major improvements in technology, speed, battery life, drop protection, and accessories – plus market-leading ruggedness in one third the size – these powerfully portable printers are a uniquely competitive solution for today's busy mobile workforces. They're everything you need for real work, real speed, real durability, real integration, and real mobility.



	Wi-Fi®	AirPrint®	USB	Bluetooth®	MFi (Bluetooth)	NFC	Battery Included
RJ-4230BL			✓	✓	✓	✓	✓
RJ-4250WBL	✓	✓	✓	✓	✓	✓	✓
RJ-4230B			✓	✓	✓	✓	
RJ-4250WB	✓	✓	✓	✓	✓	✓	

## Key features



**Performance:** Wear, carry, or mount this lightweight printer with a reinforced metal belt clip, versatile docking connectors, and fast-release docking points.



**Support:** Reinforced parts, industrial-grade buttons, molded rubber housing, and enhanced drop protection take durability to a new level.



**Powerful:** Enhanced print speeds up to 5ips, industry-leading battery life and a real-time battery status indicator help boost efficiency.



**Easy to use:** Experience simple loading, one-touch pairing, and remote updates and configuration with the free Mobile Deploy app<sup>1</sup>.



**Connected: Bluetooth®** Get connected easily with Wireless Technology 4.2 (Classic/LE/MFi) and Wi-Fi® (802.11 a/b/g/n) connectivity options, plus NFC for easy device pairing and AirPrint®.

<sup>1</sup>Internet required

Learn more about  
the RuggedJet Series



- eCitations
- Parking violations
- Accident/crime scene information
- Evidence labels
- Warning notices
- Shipping labels

- Serial number labels
- Picking & packing labels
- Shipping labels
- Barcode labels
- Tool/parts identification
- Component labels
- UL/CSA recognized labels



Extend the useful life of your printer by adding an extended service program at any point while your printer is still under warranty\*.

BrotherMobileSolutions.com

	RJ-4230BL	RJ-4250WBL
<b>General</b>		
<b>Box Contents</b>	Printer, Belt clip, Documents, Roll Holder Stop, Li-ion Battery (PABT006)	
<b>Dimensions (W x H x L)</b>	6.02" (W) x 6.26" (D) x 2.68" (H) 153mm (W) x 159mm (D) x 68mm (H)	
<b>Weight</b>	1.58lbs (717g) without battery, 1.87lbs (850g) with battery	
<b>Printer Memory</b>	RAM 256MB, Flash 64MB (Available 42MB)	
<b>Control panel</b>	1 LED w/4 Buttons, Mono LCD with Back Light	
<b>SDK Support</b>	Android™ 4.0.3 or later; iOS 7 or later	
<b>Operating Temperature/Humidity</b>	-4°F to 131°F/-20°C to 55°C / 10% to 90% non-condensing, Max wet bulb: 27° C	
<b>Drop Protection</b>	6.88' (2.1m) drop, MIL 810 standard shock vibration, Tumble 1 meter 500 times (Under Brother Standard Test Environment)	
<b>Environmental</b>	IP54	
<b>Battery</b>	Rechargeable Li-ion smart battery:7.2V, 3000mAh	
<b>Charging</b>	4 hours (full charge); 300 cycles (to 50%)	
<b>Charging Options</b>	AC adapter (15 V), Cigarette car adapter or Wired type (12V (DC))	
<b>EMI (Radio Interference)</b>	FCC Part15 Class B	
<b>Safety</b>	UL, CE, CSA	

## Connectivity

<b>Standard Interfaces</b>	USB Ver.2.0 (Full Speed) (mini-B type), Bluetooth Ver. 4.2, MFi, NFC Pairing	USB Ver.2.0 (Full Speed) (mini-B type), Bluetooth Ver. 4.2, MFi, NFC Pairing, Wireless LAN IEEE 802.11 a/b/g/n and Wireless LAN Security
<b>Wireless Security</b>	N/A	Authentic method (encryption scheme) *Infrastructure mode; Open System (None/WEP64/WEP128); Common Key Authentication (WEP); WPA/WPA2-PSK (TKIP+AES), EAP-FAST (TKIP/AES), PEAP (TKIP/AES) *3, EAP-TLS (TKIP/AES), EAP-TTLS (TKIP/AES); Authentic method (encryption scheme) *Wireless direct mode; WPA2-PSK (AES)

	RJ-4230BL	RJ-4250WBL
<b>Printing</b>		
<b>Print technology</b>	Direct Thermal	
<b>Print Head Resolution</b>	203 dpi x 203dpi	
<b>Print Engine speed</b>	Maximum 5 ips (127mm/sec)	
<b>Media/Print Width</b>	4.09" (104mm)	
<b>Resident Barcodes</b>	Linear: CODE 39, Intlv 2 of 5, EAN-8, EAN-13, UPC-A, UPC-E, UPC and EAN extension, CODABAR, CODE 128, GS1-128(UCC/EAN 128), Postnet, GS1 Databar (RSS14, RSS14 Stacked, RSS14 Truncation, RSS14 Stacked Omnidirection), GS1 Databar (RSS Limited), GS1 Databar (RSS Expanded, RSS Expanded Stacked), Code93, MSI/Plessey, Intelligent Mail Barcode 2 Dimensional: QR Code (model 1, model 2, micro QR), Maxi code, PDF417 (Standard, Truncate), MicroPDF417, Data Matrix(Square, Rectangular), Aztec Code	
<b>Printer Sensors</b>	Transmissive, Reflective, Continuous Receipt, Gap/Black Mark Labels and Tags	
<b>Media Type</b>	Paper and Synthetic Receipts, Labels, Tags	
<b>Media Roll Size</b>	Roll Diameter (Max) 2.28" (58mm), Core Diameter (Min) Receipt: 0.50" (12.7mm); Label: 1.00" (25.4mm)	
<b>Cutter</b>	Tear Up and Tear Down Bars	
<b>Print Length (Max.)</b>	118.1" (3M)	
<b>Print Length (Min.)</b>	1" (12.7mm)	
<b>Media Width (Max.)</b>	4.45" (113mm)	
<b>Media Width (Min.)</b>	1.77" (45mm)	
<b>Max. Thickness</b>	Receipt: 2.3mil to 3.5mil (0.058mm to 0.090mm); Tag: 3.5mil to 5.3mil (0.090mm to 0.135mm); Label: 3.2mil to 6.7mil (0.080mm to 0.170mm)	
<b>Fonts</b>	14 Bitmap, 4 Outline Fonts (Internal), Downloadable with Font Manager	
<b>Supported Printer Driver</b>	Windows 7, Windows 8, Windows 8.1, Windows 10, Windows Server 2008/ 2008R2, Windows Server 2012 / 2012 R2/ 2016	
<b>Supported Command</b>	Raster, ESC/P, P-touch Template, ZPL emulation, CPCL emulation (CPCL page print mode / CPCL line print mode)	

Images are for illustrative purposes only. Actual output (such as font and margins) may vary. All specifications subject to change without notice.

Brother is a trademark or registered trademark of Brother Industries, Ltd, in the United States. All other trademarks and registered trademarks are the properties of their respective companies.

© 2021 Brother Mobile Solutions, Inc. 11030 Circle Point Road, Suite 100, Westminster, CO 80020